



# APPLIED THERMAL ENGINEERING



Editor-in-Chief: *David A. Reay*

DESIGN . PROCESSES . EQUIPMENT . ECONOMICS

Also available on

SCIENCE @ DIRECT®

[www.sciencedirect.com](http://www.sciencedirect.com)

# APPLIED THERMAL ENGINEERING

DESIGN · PROCESSES · EQUIPMENT · ECONOMICS

Volume 28, Numbers 11–12

August 2008

## CONTENTS

- |  |      |   |
|--|------|---|
| W. CHEN and W. LIU   | 1251 | Numerical analysis of heat transfer in a passive solar composite wall with porous absorber  |
| D. PENG, X. ZHANG and Y. YIN                                   | 1259 | Theoretical storage capacity for solar air pretreatment liquid collector/regenerator  |
| A. BAÏRI   | 1267 | On the Nusselt number definition adapted to natural convection in parallelogrammic cavities   |
| H.-T. HU, G.-L. DING and K.-J. WANG                            | 1272 | Measurement and correlation of frictional two-phase pressure drop of R410A/POE oil mixture flow boiling in a 7 mm straight micro-fin tube |
| H. YASAR, H. S. SOYHAN, H. WALMSLEY, B. HEAD and C. SORUSBAY   | 1284 | Double-Wiebe function: An approach for single-zone HCCI engine modeling   |
| F. KUZNIK, J. VIRGONE and J. NOEL                              | 1291 | Optimization of a phase change material wall-board for building use   |
| D. SONG, T. KIM, S. SONG, S. HWANG and S.-B. LEIGH             | 1299 | Performance evaluation of a radiant floor cooling system integrated with dehumidified ventilation   |
| Y.-H. LIN, S.-W. KANG and H.-L. CHEN                           | 1312 | Effect of silver nano-fluid on pulsating heat pipe thermal performance  |
| V. A. PRISYAZHNIUK   | 1318 | The turbine plant efficiency: Maximum efficiency attained and the share of individual stages  |
| M. R. JAFARI NASR and A. SHAFEGHAT                             | 1324 | Fluid flow analysis and extension of rapid design algorithm for helical baffle heat exchangers  |
| G. SINGHAL, A. L. DAWAR and P. M. V. SUBBARAO                  | 1333 | Application of profiled ejector in chemical lasers  |
| B. S. MOHAN, M. P. MAIYA and S. TIWARI                         | 1342 | Performance characterisation of liquid desiccant columns for a hybrid air-conditioner   |
| T. T. CHOW, W. HE, A. L. S. CHAN, K. F. FONG, Z. LIN and J. JI | 1356 | Computer modeling and experimental validation of a building-integrated photovoltaic and water heating system                              |
| Y.-W. YAN, J.-X. ZHAO, J.-Z. ZHANG and Y. LIU                  | 1365 | Large-eddy simulation of two-phase spray combustion for gas turbine combustors  |
| C. HONG and Y. ASAKO   | 1375 | Heat transfer characteristics of gaseous flows in microtube with constant heat flux   |

*[continued on inside back cover]*



1359-4311(200808)28:11-12;1-S

Indexed/Abstracted in: *Appl. Mech. Rev., Res. Alert, Cam. Sci. Abstr., Chemical Abstracts Service, Curr. Cont./Eng. Tech. & Appl. Sci., Curr. Tech. Ind., EIC Intell., Eng. Ind., Metals Abstr., Curr. Cont. SCISEARCH Data., TCEA*