Peopl's Democratic Republic of Algeria
Ministry of Higher and Scientific Research
University Saad Dahleb Blida 1
Faculty of Mathematics

Graduation Thesis

Presented for obtaining a Master's degree

In : Mathematics

Speciality : Operationnal Research

By : SNOUBRI MEROUA

Theme

Minimizing Customers' Waiting Time in Vehicle Routing Problem with Unit Demands

In front of the jury composed by:

Mr. Frihi R	President	Univ blida 1
Ms. Arrache S	Examiner	Univ blida 1
Mr. Boudjemaa R	Supervisor	Univ blida 1
Ms. Saou G	Advisor	SNC Bencherchali

2024/2025

DEDICATION

To the loving memory of my father,
whose strength and wisdom continue to guide me
even though you're no longer here to see this day.

To my dearest mother,
your endless sacrifices and unconditional love
made every step of this journey possible.

To my wonderful sisters,
your constant support and encouragement
gave me strength when I needed it most.

To my friends Amira, Maria, Ammar
I thank you immensely and wish you a life full of happiness.

This achievement belongs to all of you
as much as it does to me.

ACKNOWLEDGEMENT

*First of all, I thank **Allah the Almighty**,*
for giving me the courage and patience
necessary to complete this work.

I would especially like to thank my supervisor,
***Mr. Boudjemaa Redouane**,*
for the expert guidance he provided,
as well as for his patience and encouragement.
His critical eye was invaluable
in structuring the work
and improving the quality of its various sections.

I would also like to express my sincere gratitude
*to my advisor, **Ms. Saou Goussem**,*
for her immense help,and for all the advice and information she provided
with unmatched patience and professionalism.

*A special thank you goes to **Mr. Bencharchali Ismail**,*
for helping me secure this internship
*at **SNC Bencherchali Frères**.*

I sincerely thank the members of the jury
for taking the time to read my work
and for their valuable comments
and support during the evaluation.

ABSTRACT

This thesis aims to study a mathematical optimization model for minimizing customer waiting times in the context of the Unit Demand Vehicle Routing Problem. A Mixed Integer Linear Programming (MILP) formulation is developed to tackle the problem, focusing on customer-centric objectives rather than traditional cost minimization. The model is implemented using the commercial solver IBM ILOG CPLEX, which allows for solving medium-sized benchmark instances derived from the TSPLIB. The obtained results are then compared with those from existing literature to evaluate the effectiveness and performance of the proposed approach. This work highlights the importance of integrating service quality metrics such as latency into modern vehicle routing models.

Keywords: Vehicle Routing Problem (VRP), Unit Demand, Customer Waiting Time, Mixed Integer Linear Programming (MILP), CPLEX, Exact Methods, Service Optimization, Latency Minimization, Combinatorial Optimization.

RÉSUMÉ

Cette thèse a pour objectif l'étude d'un modèle d'optimisation mathématique visant à minimiser le temps d'attente des clients dans le cadre du Problème de Tournées de Véhicules avec Demande Unitaire. Une formulation en Programmation Linéaire en Nombres Entiers Mixtes (MILP) est développée pour traiter le problème, en mettant l'accent sur des objectifs centrés sur le client plutôt que sur la simple minimisation des coûts. Le modèle est implémenté en utilisant le solveur commercial IBM ILOG CPLEX, ce qui permet de résoudre des instances de référence de taille moyenne extraites de la bibliothèque TSPLIB. Les résultats obtenus sont ensuite comparés à ceux de la littérature existante afin d'évaluer l'efficacité et la performance de l'approche proposée. Ce travail met en évidence l'importance d'intégrer des indicateurs de qualité de service, tels que la latence, dans les modèles modernes de tournées de véhicules.

Mots-clés : Problème de tournées de véhicules, demande unitaire, temps d'attente des clients, programmation linéaire en nombres entiers mixtes, CPLEX, méthodes exactes, optimisation du service, minimisation de la latence, optimisation combinatoire.

ملخص

تهدف هذه الأطروحة إلى دراسة نموذج رياضي من أجل تقليل أوقات انتظار الزبائن في سياق مشكلة توجيه المركبات ذات الطلب الأحادي. تم تطوير نموذج باستخدام البرمجة الخطية بالأعداد الصحيحة المختلطة لحل المشكلة، مع التركيز على أهداف موجهة نحو الزبون بدلاً من تقليل التكاليف فقط. تم تنفيذ النموذج باستخدام البرنامج التجاري، مما سمح بحل عينات ممثلة متوسطة الحجم. تم بعد ذلك مقارنة النتائج التي تم الحصول عليها مع نتائج موجودة في الأدبيات من أجل تقييم فعالية وأداء النهج المقترح. يبرز هذا العمل أهمية دمج مقاييس جودة الخدمة مثل زمن الانتظار في نماذج توجيه المركبات الحديثة.

الكلمات المفتاحية: مشكلة توجيه المركبات، الطلب الأحادي، وقت انتظار الزبائن، البرمجة الخطية بالأعداد الصحيحة المختلطة، طرق دقيقة، تحسين الخدمة، التحسين التركيبي.

CONTENTS

LIST OF FIGURES

LIST OF TABLES

ABBREVIATIONS AND NOTATIONS

Abbreviations

CO	Combinatorial optimization.
TSP	Travelling salesman .
VRP	Vehicle routing problem.
CVRP	Capacitated Vehicle Routing Problem.
UDCCVRP	Unit Demand Customer-Centric Vehicle Routing Problem.
LP	Linear Programming.
ILP	Integer Linear Programming.
MILP	Mixed Integer Linear Programming.
NP-hard	Non-deterministic Polynomial-time hard.
NP-complete	Non-deterministic Polynomial-time complete.

Notations

$\mathbb{R}$	Set of real numbers

GENERAL INTRODUCTION

Operational Research (OR) is a multidisciplinary scientific discipline that leverages advanced analytical techniques to optimize decision-making in complex systems. Drawing from mathematics, statistics, computer science, and management science, OR provides a structured approach to solving real-world problems in diverse domains such as logistics, transportation, healthcare, and resource allocation. By formulating mathematical models and employing computational algorithms, OR enables decision-makers to achieve efficient and effective solutions that balance competing objectives, such as cost, time, and resource utilization. The field has evolved significantly since its origins during World War II, where it was used to optimize military operations, and now plays a pivotal role in modern industries, addressing challenges ranging from supply chain management to urban planning.

A central pillar of Operational Research is combinatorial optimization, a subfield of discrete mathematics concerned with finding the best solution from a finite, often vast, set of feasible solutions. Combinatorial optimization problems are characterized by discrete decision variables and constraints, such as selecting specific routes, scheduling tasks, or assigning resources. These problems are prevalent in industries where decisions involve choosing among discrete alternatives, such as determining optimal delivery routes or assigning personnel to shifts. Due to the finite yet exponentially large solution spaces, many combinatorial optimization problems, including the Traveling Salesman Problem (TSP) and the Vehicle Routing Problem (VRP), are classified as NP-hard, posing significant computational challenges. To address these, researchers employ a range of exact methods, such as Branch-and-Bound ,Branch-and-Cut, as well as heuristic and metaheuristic approaches, to find optimal or near-optimal solutions within reasonable computational timeframes. This thesis focuses on one such prob-

lem, leveraging combinatorial optimization techniques to address a customer-centric routing challenge.

Among the myriad challenges in combinatorial optimization, the Vehicle Routing Problem (VRP) stands as a cornerstone due to its wide-ranging applications in logistics and supply chain management. First introduced by Dantzig and Ramser in 1959 [25], the VRP involves designing optimal delivery routes from one or more depots to a set of geographically dispersed customers, subject to constraints such as vehicle capacity, time windows, and customer demands. The VRP generalizes the Traveling Salesman Problem (TSP) by incorporating multiple vehicles and additional operational constraints, making it a more complex and practical problem for real-world logistics scenarios. Variants of the VRP, such as the Capacitated VRP (CVRP)[10], VRP with Time Windows (VRPTW) [33], and Stochastic VRP (SVRP)[32], have been developed to address specific practical requirements, such as limited vehicle capacities, time-sensitive deliveries, or uncertain demands. In recent years, the focus of VRP research has shifted toward service-oriented objectives, particularly in industries like e-commerce, emergency services, and perishable goods distribution, where customer satisfaction is paramount. This thesis investigates a specific variant, the Unit Demand Customer-Centric Vehicle Routing Problem (UDCCVRP), which prioritizes minimizing customer waiting times, or latency, over traditional cost-based metrics like total distance or vehicle usage. By focusing on customer waiting time, the UDCCVRP aligns with the growing emphasis on enhancing customer experience in modern logistics systems, particularly in time-critical applications such as last-mile delivery and emergency response.

The motivation for this research stems from the increasing demand for customer-centric logistics solutions in today's fast-paced, service-driven economy. With the rise of e-commerce platforms and on-demand delivery services, customers expect rapid and reliable service, making the minimization of waiting times a critical performance metric. Similarly, in emergency logistics, such as ambulance dispatching or disaster response, reducing response times can have life-saving implications. Traditional VRP models, which primarily optimize for operational efficiency, often overlook the customer's perspective, leading to suboptimal service quality. The UDCCVRP addresses this gap by redefining the objective function to minimize the cumulative waiting time experienced by customers, ensuring equitable and timely service delivery. This customer-focused approach not only enhances service quality but also contributes to operational fairness, a critical consideration in industries where customer satisfac-

tion directly impacts business success.

This thesis aims to contribute to the field of service-oriented logistics by applying an existing Mixed Integer Linear Programming (MILP) model for the UDCCVRP, which is designed to minimize total customer waiting time by incorporating flow-based constraints to eliminate subtours and respect vehicle capacity limits, the model offers a robust mathematical framework that prioritizes customer experience. The model is implemented using IBM ILOG CPLEX, a powerful optimization solver, and tested on benchmark instances from the TSPLIB library, ranging from 30 to 100 nodes. The computational experiments validate the model's effectiveness in achieving optimal solutions for medium-sized instances while highlighting the inherent complexity of NP-hard routing problems. The contributions of this work include a customer-centric objective function, a flow-based MILP formulation, and comprehensive computational results that demonstrate the model's scalability and practical applicability. These contributions pave the way for further research into scalable, real-time, and stochastic routing solutions that can address the dynamic challenges of modern logistics.

To systematically explore the UDCCVRP and its solution framework, this thesis is organized into the following chapters:

- **Chapter 1: Literature Review of UDCCVRP** provides a comprehensive review of the Vehicle Routing Problem and its variants, with a particular focus on the Unit Demand VRP (UDVRP) and the shift toward customer-centric objectives in the UDCCVRP. It surveys the theoretical foundations, including the classical VRP introduced by Dantzig and Ramser, and discusses key variants such as CVRP, VRPTW, and others. The chapter also explores the application of Mixed Integer Linear Programming (MILP) models, emphasizing flow-based formulations and exact solution methods like Branch-and-Bound and Branch-and-Cut. The implementation of these methods in IBM ILOG CPLEX is highlighted, along with their effectiveness in solving medium-sized instances of the UDCCVRP.

- **Chapter 2: Combinatorial Optimization and Theory of Complexity** introduces the principles of combinatorial optimization and the computational complexity of NP-hard problems, with a focus on the VRP and its precursor, the Traveling Salesman Problem (TSP). It presents mathematical formulations for both the TSP and VRP, detailing their objective functions and constraints. The chapter also explores linear programming techniques, including Linear Programming (LP) and MILP, and discusses solution methods such as the Simplex Method and Graphical

Method. The complexity of algorithms and problem classes (e.g., P, NP, NP-hard) is examined, underscoring the computational challenges of solving VRP variants and the relevance of exact methods for achieving optimal solutions.

- **Chapter 3: Modeling and Experimental Evaluation** presents a comprehensive study of the Unit Demand Customer-Centric Vehicle Routing Problem (UDC-CVRP) using a Mixed Integer Linear Programming (MILP) approach aimed at minimizing total customer waiting time (latency). The chapter begins by defining the problem setting, including sets, parameters, decision variables, and essential constraints such as flow conservation, subtour elimination, and vehicle capacity limits. The MILP model is implemented in IBM ILOG CPLEX Optimization Programming Language (OPL), with a strong focus on clarity, reproducibility, and theoretical robustness.

  Building upon the model, the chapter proceeds to evaluate its performance through computational experiments on benchmark datasets derived from the TSPLIB library, covering instances from 30 to 100 nodes. It details the experimental setup, instance generation process, and solver configuration. The model's effectiveness is analyzed using performance metrics such as objective value (total latency) and CPU time. The results highlight the model's scalability, achieving optimal solutions for medium-sized instances and demonstrating advantages over reference methods in both solution quality and computational efficiency. The chapter concludes with visualizations and comparative analyses that reinforce the practical relevance and strength of the proposed approach.

The results presented in this thesis offer a simplified introduction to the Unit Demand Customer-Centric Vehicle Routing Problem (UDCCVRP) and serve to demonstrate the applicability and effectiveness of the selected MILP model in minimizing customer waiting time across benchmark instances.

CHAPTER 1

LITERATURE REVIEW OF UDCCVRP

1.1 Introduction

The Vehicle Routing Problem (VRP) is one of the most extensively studied combinatorial optimization problems in operations research due to its wide applicability in logistics, supply chain management, and transportation planning. A significant variant of this problem is the Unit Demand Customer-Centric Vehicle Routing Problem (UDCCVRP), which focuses on minimizing customer waiting time rather than traditional cost-based metrics.

This literature review summarizes the theoretical foundations, related works, and recent advancements relevant to the UDCCVRP, particularly focusing on models that aim to reduce customer waiting times in VRPs with unit demands.

1.2 Overview of vehicle routing problem

The Vehicle Routing Problem (VRP) was first introduced by Dantzig and Ramser in 1959 [25] and has since become a cornerstone of combinatorial optimization. It involves determining optimal delivery routes from one or more depots to a set of geographically dispersed customers, subject to various constraints such as vehicle capacity, time windows, and precedence relations between customers.

1.3 Variants of vehicle routing problem

- **Capacitated VRP (CVRP)**: The CVRP addresses the problem of designing optimal routes for a fleet of identical vehicles with limited carrying capacities to serve a set of customers with known demands.[10]
- **VRP with Time Windows (VRPTW)**: In the VRPTW, each customer must be visited within a specific time window. Vehicles may have to wait if they arrive early and are not allowed to arrive late.[33]
- **VRP with Backhauls (VRPB)**: The VRPB extends the basic VRP by incorporating both deliveries to customers and pickups from them, typically requiring deliveries to be completed before any pickups.[34]
- **Split Delivery VRP (SDVRP)**: In the SDVRP, customer demand can be split among multiple vehicles, allowing a customer to be visited more than once if needed.[35]
- **Periodic VRP (PVRP)**: The PVRP involves planning routes over a multi-day horizon, where each customer has a required visit frequency during the planning period.[36]
- **Stochastic VRP (SVRP)**: The SVRP introduces randomness into the problem, such as uncertain customer demand or travel times, requiring solutions that account for probabilistic elements.[32]

In all these variants, the primary objective is usually cost minimization, such as reducing fuel consumption, labor costs, or vehicle usage.

1.4 Parameters of the VRP

The VRP is characterized by :

Network

The transport network enables the flow of individuals, freight, or information , it can be considered the backbone of a system designed to establish a form of communication.this network can be represented as a complete graph, which may be either symmetric or asymmetri,the nodes represent the customers, characterized by their geo-

graphical position (coordinates (x, y)), and the edges represent the paths connecting the various customers,under certain constraints, this graph may be directed.

Customers

A customer is characterized by their demand, which may be a request for a service or for products (goods). These products can be of a single type or multiple types. The total demand of all customers on the same route must not exceed the vehicle's capacity Q. A customer is also defined by their location in space. Finally, the demand can be deterministic (the quantity requested by the customer is fixed and known by the distributor) or uncertain (stochastic).

Vehicle fleet

The first characteristic of the fleet is its size (the number of vehicles it contains). The second is its homogeneity—whether the vehicles have the same carrying capacity and transportation cost—or its heterogeneity, in which case the vehicles have different capacities and/or transportation costs.

Objective Function

The most common objectives are either the minimization of the number of vehicles used or the minimization of the total distance traveled by the vehicles. Other objectives may also be considered:

- Minimization of the total tour time, waiting time, delay time, service time, etc.
- Minimization of the number of vehicles.
- Minimization of the total cost of the tour, including fixed costs such as vehicle depreciation, driver salaries, vehicle expenses, etc., and variable costs such as penalties for delays, particularly in the case of VRPTW (Vehicle Routing Problem with Time Windows).
- Maximization of the profit generated by the tour in the case of product collection from customers.
- Maximization of service quality.
- Maximization of vehicle load utilization for the tours.

1.5 Introduction to the Unit Demand VRP (UDVRP)

The Unit Demand Vehicle Routing Problem (UDVRP) functions as a specific instance of the Capacitated Vehicle Routing Problem (CVRP) by assuming every customer needs one product unit. The model becomes easier to solve since the vehicle capacity limitation directly becomes a maximum number of customers which each route can handle. A vehicle with a capacity of 10 units can serve only 10 customers during each route. Because customer demands are identical and known in advance, the focus shifts from managing varying load sizes to optimally clustering and sequencing customers. This uniformity allows the use of specialized optimization strategies and can improve computational efficiency when solving large-scale instances. The UDVRP represents a modified mTSP version [26]where vehicles begin and end their routes at the depot while being restricted by the number of customers instead of distance or time constraints. The problem shares strong connections with both combinatorial optimization principles and standard graph-theoretic problem formulations.

1.6 Shift to Customer-Centric Objectives: introducing UDCCVRP

While most VRP studies focus on operational efficiency, there has been growing interest in service-oriented optimization, where the quality of service especially customer satisfaction is prioritized. One key metric in this context is customer waiting time, also known as latency.

The Unit Demand Customer-Centric VRP (UDCCVRP) redefines the objective function to minimize total customer waiting time, i.e., the sum of the times at which each customer receives their delivery. This shift reflects a broader trend in logistics toward customer-centric supply chains, especially in industries like e-commerce, emergency services, and last-mile delivery.

1.6.1 Mathematical Modeling

1.6.2 MILP Modeling for UDCCVRP

A Mixed-Integer Linear Programming (MILP) model includes both continuous and integer (often binary) decision variables, and all relationships between them are ex-

pressed as linear equations or inequalities. This structure provides the flexibility to accurately model vehicle routing problems while enabling the use of powerful solvers like CPLEX .

In the context of the UDCCVRp, the MILP model typically includes the following components:

- **Binary decision variables** to indicate whether a vehicle travels directly from customer i to customer j. These variables form the foundation for route construction.
- **Flow-based constraints** to eliminate subtours (i.e., infeasible loops that do not include the depot). These are often formulated using either flow conservation .
- **Capacity constraints** that restrict the number of customers visited on a route, ensuring that no vehicle exceeds its maximum allowable capacity. Since demand is unitary, this becomes a limit on the number of customers served per vehicle.
- **Continuous variables** to track the sequence or flow of goods or customers, often used to model waiting times or arrival order. These help quantify service quality and are essential in customer-centric formulations.

1.6.3 Flow-Based Formulations

The formulation uses flow variables f_{ij} to represent the number of customers remaining to be visited after traversing arc (i, j). These flow variables help eliminate subtours without the need for explicit constraints, improving model efficiency.

$$\sum_{j \in V} f_{ij} - \sum_{j \in V} f_{ji} = 1 \quad \forall i \in V \setminus \{0\} \tag{1.1}$$

1.6.4 Subtour Elimination Techniques

Subtours are eliminated through:

- Flow conservation equations: flow-based models introduce continuous variables to represent the sequence or load traveling through the route, in UDCCVRP these variables often represent the order in which customers are served.
- Valid inequalities : When modeling larger instances, it's inefficient to add all possible subtour elimination constraints beforehand.

- Branch-and-cut algorithms :Advanced solvers like CPLEX use branch-and-cut algorithms that dynamically add subtour elimination constraints when needed. They solve a relaxed MILP, detect subtours, add necessary cuts, and continue branching until a valid, optimal solution is found. This is particularly effective in UDCCVRP to avoid a combinatorial explosion of constraints.

1.7 Exact Solution Methods

1.7.1 Branch-and-Bound (B&B)

Branch-and-Bound is a classical exact algorithm used to solve combinatorial optimization problems such as the Vehicle Routing Problem (VRP). The method systematically explores the solution space by dividing it into smaller subproblems (branching) and computing lower and upper bounds for each. If a sub-problem cannot produce a better solution than the current best (bound), it is pruned from the search. B&B ensures optimality but can be computationally intensive for large instances. It is especially useful for solving small to moderately sized VRPs where the solution space is still tractable.

1.7.2 Branch-and-Cut (B&C)

Branch-and-Cut enhances the B&B framework by integrating cutting plane methods. In addition to branching, it dynamically adds valid inequalities, known as cuts, to eliminate infeasible or suboptimal regions of the solution space—particularly those involving subtours or violated capacity constraints. This approach tightens the Linear Programming (LP) relaxation of the problem, allowing the solver to converge faster. B&C is widely used in state-of-the-art solvers like IBM ILOG CPLEX and is particularly effective for solving medium-sized instances of the UDCCVRP (up to approximately 100 customers).

1.7.3 CPLEX Implementation

In this thesis, the MILP model for the UDCCVRP is implemented using IBM ILOG CPLEX, a high-performance solver that internally applies the Branch-and-Cut algorithm. CPLEX efficiently handles the complexity of the problem by combining LP relaxation, automatic cut generation, and intelligent branching strategies. The model is tested on benchmark instances adapted from the TSPLIB library. Results show that

the implementation can solve instances with up to 100 nodes to proven optimality within reasonable computational time.

1.8 Applications and Impact

1.8.1 Application Domains of VRP

The Vehicle Routing Problem (VRP) has become a cornerstone of optimization research due to its vast range of real-world applications [24]

- **Widespread Applications**: TSP and VRP are used across various industries to optimize logistics and reduce supply chain costs .
- **Cost Efficiency**: Transportation represents nearly 30% of production costs, making VRP crucial for minimizing expenses .
- **Everyday Uses**: Common applications include school transport, employee shuttles, waste collection, milk and mail delivery, and food distribution.
- **Urgent Services**: VRP is essential in time-sensitive areas like mobile medical services and pharmaceutical distribution, where serving customers quickly is more important than minimizing distance .
- **Time Constraints**: These problems often involve strict time windows, especially in pickup scenarios.
- **Technology Integration**: VRP plays a key role in data routing for computer networks and aircraft scheduling .
- **Computational Challenge**: Despite extensive research, many large VRP instances remain too complex to solve exactly, even with advanced computing power.

1.9 Thesis Contributions

1.9.1 Objective Function

Introduces a customer-centric objective that minimizes total waiting time instead of traditional metrics like total distance or number of vehicles.[43]

1.9.2 Flow-Based MILP Model

MILP formulation incorporating:

- Flow conservation constraints
- Subtour elimination
- Capacity limits

1.9.3 Computational Experiments

- Model implemented using IBM ILOG CPLEX
- Tested on benchmark datasets derived from TSPLIB
- Optimal solutions obtained for instances with up to 100 nodes

1.10 conclusion

This chapter provided a comprehensive literature review of the Unit Demand Customer-Centric Vehicle Routing Problem (UDCCVRP), highlighting the shift from traditional cost-minimization models to approaches prioritizing customer waiting time reduction.In the next chapter, we will go into detail on the theoretical side.

CHAPTER 2

COMBINATORIAL OPTIMIZATION AND THEORY OF COMPLEXITY

2.1 Combinatorial Optimization Problem

Combinatorial optimization is a field of discrete mathematics that deals with solving problems aimed at maximizing (e.g., gain, performance: maximization problems) or minimizing (e.g., loss, cost: minimization problems) an objective function under certain constraints [1]. It involves seeking the best solution (or set of best solutions) among all possible solutions, with the goal of finding an optimal or near-optimal solution within a reasonable execution time. This "best" is evaluated based on one or more quality criteria formulated in an objective function [2]. Although the set of feasible solutions is generally finite, it often has a very large cardinality, which justifies the difficulty of enumerating such solutions, requiring very long execution times. Optimization problems are primarily divided into two categories: those with continuous variables and those with discrete variables. In the case of "combinatorial optimization" problems, we refer to discrete variables [3]. The type of variables and the nature of the constraints determine the complexity of the problem. These problems are generally difficult to solve, and most belong to the class of NP-hard problems.

A combinatorial optimization problem can be defined by the following elements:

- A set of feasible solutions S.
- An objective function $f : S \to \mathbb{R}$ that assigns a value to each solution.

- An optimization criterion: minimization or maximization of the objective function.

The goal is to find an optimal solution $s^* \in S$ such that:

$$f(s^*) = \min_{s \in S} f(s) \quad \text{or} \quad f(s^*) = \max_{s \in S} f(s)$$

2.1.1 Some Classic Combinatorial Optimization Problems

- **Traveling Salesman Problem (TSP)**
  The TSP is a well-known combinatorial optimization problem that aims to find the shortest possible route for a salesman to visit a given set of cities, exactly once each, and return to the starting point, minimizing the total travel cost or distance [38].

- **Vehicle Routing Problem (VRP)**
  The VRP generalizes the TSP by involving a fleet of vehicles that must deliver goods to a set of customers while minimizing operational costs (e.g., distance, time), and satisfying constraints such as vehicle capacities and time windows[10].

- **Knapsack Problem**
  The Knapsack Problem involves selecting a subset of items, each with a value and weight, to place in a knapsack such that the total value is maximized without exceeding a weight limit [39].

- **Bin Packing Problem**
  This problem seeks the minimum number of fixed-capacity bins required to pack a set of items[40] .

- **Timetabling Problem**
  The timetabling problem involves assigning events (e.g., lectures, exams) to timeslots and locations while avoiding conflicts, satisfying availability constraints, and optimizing preferences [41].

2.2 Vehicle routing problem

2.2.1 Definition Of Travelling Salesman Problem

The Traveling Salesman Problem (TSP) is one of the most widely studied combinatorial optimization problems from which VRP derives, consists of a salesman and a set of cities. The salesman has to visit each one of the cities starting from a certain one (e.g. the hometown) and returning to the same city. The challenge of the problem is that the traveling salesman wants to minimize the total length of the trip. [38]



Figure 2.1: Illustration of TSP

Figure 2.1 : the nodes (labeled 1 to 16 in blue) are connected by red lines, forming a path that visits each node exactly once before returning to the central node in black "A" (likely the starting/ending point)

2.2.2 Definition of Vehicle Routing Problem

The *Vehicle Routing Problem* (VRP) is defined as the problem of designing optimal delivery routes from one or several depots to a number of geographically scattered cities or customers, subject to side constraints. Due to the introduction of a wide variety of constraints in terms of capacity, route length, time windows, and precedence relations between customers, it is pretty hard to find a generally accepted definition of VRP .

In fact, the VRP can be seen as a particular case and an extension of the well-known *Traveling Salesman Problem* (TSP), from which it originated. VRP extends the TSP by introducing additional operational constraints and multiple routes instead of a single tour. Moreover, VRP can also be described as a combination of two well-studied problems, namely the Traveling Salesman Problem (TSP) and the *Bin Packing*

Problem (BPP), since it conceptually lies at the intersection of these two well-studied problems.[10]



Figure 2.2: Illustration of VRP

Figure (2.2) : the figure illustrates a Vehicle Routing Problem (VRP) solution, where multiple vehicles (depicted as trucks) start from a central "Depot" (shown in orange) to deliver to various "Customer" locations (blue dots). Each vehicle follows a specific route connecting a subset of customers before returning to the depot.

2.2.3 Mathematical Formulation of TSP

Let:

- $G = (X, U)$ be a directed graph,
- $X = \{1, 2, \ldots, n\}$ be the set of vertices (e.g., cities or customers),
- $U \subseteq X \times X$ be the set of directed arcs,
- C_{ij} be the cost associated with arc (i, j),
- $x_{ij} \in \{0, 1\}$ be a binary variable equal to 1 if arc (i, j) is used in the solution, and 0 otherwise.

Objective Function:

$$\min \sum_{i=1}^{n} \sum_{j=1}^{n} C_{ij} x_{ij} \tag{2.1}$$

Subject to:

$$\sum_{i \in X} x_{ij} = 1 \quad \forall j \in X \tag{2.2}$$

$$\sum_{j \in X} x_{ij} = 1 \quad \forall i \in X \tag{2.3}$$

$$\sum_{i \in S} \sum_{j \in S} x_{ij} \leq |S| - 1 \quad \forall S \subset X,\ 2 \leq |S| \leq n-2 \tag{2.4}$$

$$x_{ij} \in \{0,1\} \quad \forall i \in X,\ \forall j \in X \tag{2.5}$$

The objectif function (2.1) corresponds to minimization of the total distance traveled,constraints (2.2) and (2.3) ensure that the salesman visits each vertex (client) exactly once,constraint (2.4) prevents the formation of subtours (incomplete cycles that do not visit all cities).

2.2.4 Mathematical formulation of VRP

Many formulations of the Vehicle Routing Problem (VRP) exist in the literature. The common point of all these formulations is the representation of the vehicle routing problem in the form of a directed graph. The graphical representation of the classical VRP is described as follows:

Let $G = (X, U)$ be a directed graph where:

- X represents the set of vertices of the graph G , X = {1,2,. . . , n} it represents the customers and the depot(s) of the VRP, $X = X \cup \{0\}$ and $|X| = n + 1$.

- U, the set of arcs of the graph, represents the paths connecting customers to each other and to the VRP depot, $|U| = ((n+1) \cdot n)/2$.

- A weighting can be applied to the vertices (or arcs) to define the quantity demanded by the customer (resp. the distance between two customers or the travel time, etc.).

The most commonly used mathematical formulation of the classical VRP in the literature is the one adopted by Laporte [8], Rego and Roucairol [9], Toth and Vigo [10], Crainic and Semet [11]. Indeed, it requires defining $n \times n$ binary decision variables,

with three indices, as follows [12]

$$x_{ij}^k = \begin{cases} 1 & \text{if arc } (i,j) \text{ is traversed by the } k^{\text{th}} \text{ vehicle} \\ 0 & \text{otherwise} \end{cases} \tag{2.6}$$

In other words:

$$x_{ij}^k \in \{0,1\}; \quad i = 0,\dots,n; \quad j = 0,\dots,n; \quad k = 1,\dots,m \tag{2.7}$$

The problem is modeled as follows:

$$\text{Minimize} \quad \sum_{i=1}^{n}\sum_{j=1}^{n} c_{ij} \sum_{k=1}^{m} x_{ij}^k \tag{2.8}$$

$$\text{Subject to:} \quad \sum_{i=1}^{n}\sum_{k=1}^{m} x_{ij}^k = 1, \quad j = 2,\dots,n \tag{2.9}$$

$$\sum_{j=1}^{n}\sum_{k=1}^{m} x_{ij}^k = 1, \quad i = 1,\dots,n \tag{2.10}$$

$$\sum_{i=1}^{n} x_{ip}^k - \sum_{j=1}^{n} x_{pj}^k = 0, \quad k = 1,\dots,m; \quad p = 1,\dots,n \tag{2.11}$$

$$\sum_{i=1}^{n} q_i \left(\sum_{j=1}^{n} x_{ij}^k \right) \leq Q_k, \quad k = 1,\dots,m \tag{2.12}$$

$$\sum_{i=1}^{n} s_{ki} x_{ij}^k + \sum_{i=0}^{n}\sum_{j=0}^{n} t_{ij}^k x_{ij}^k \leq T_k, \quad k = 1,\dots,m \tag{2.13}$$

$$\sum_{j=1}^{n} x_{0j}^k \leq 1, \quad k = 1,\dots,m \tag{2.14}$$

$$\sum_{i=1}^{n} x_{i0}^k \leq 1, \quad k = 1,\dots,m \tag{2.15}$$

$$\sum_{i\in S}\sum_{j\in S} x_{ij}^k \leq |S| - 1, \quad \text{for all } S \subseteq N, \text{ and } 2 \leq |S| \leq n-1 \tag{2.16}$$

Here :

- n : number of customers;
- m : number of vehicles ($m \leq n$);
- Q_k : capacity of the k^{th} vehicle;

- T_k : maximum route duration for the k^{th} vehicle;
- q_j : demand of the j^{th} customer, with $q_0 = 0$;
- s_{kj} : service time of the j^{th} customer by the k^{th} vehicle ($s_{k0} = 0$);
- t_{ij} : travel time from customer i to customer j ($t_{kj} = +\infty$ if not reachable);
- d_{ij} : distance between customer i and customer j ($d_{kj} = +\infty$ if not reachable);
- c_{ij} : cost of traveling from customer i to customer j.

Formula (2.8) represents the objective function of the classical VRP. Generally, the objective is to minimize the total cost of the routes. Formulas (2.9) to (2.16) represent the constraints of the problem: Constraints (2.9) and (2.10) ensure that each customer is served exactly once and by only one vehicle. Constraint (2.12) ensures that the vehicle's capacity is not exceeded. Constraint (2.13) guarantees that the total duration of a route never exceeds its maximum allowed duration. Constraints (2.14) and (2.15) ensure that the availability of each vehicle is respected: a vehicle can only leave the depot and return to it once.The final constraint(2.16) ensures the elimination of subtours.

2.3 Linear Programming (LP)

Linear Programming (LP), or linear optimization, is the foundation of MILP, It is a method to achieve the best outcome (such as maximum profit or lowest cost) in a mathematical model whose requirements and objective are represented by linear relationships. [28] Linear programming is a special case of mathematical programming , in which the objective function is linear in the unknowns and the constraints consist of linear equalities and linear inequalities. The exact form of these constraints may differ from one problem to another, but as shown below, any linear program can be transformed into the following standard form:

$$
\begin{aligned}
\text{minimize} \quad & c_1 x_1 + c_2 x_2 + \cdots + c_n x_n \\
\text{subject to} \quad & a_{11} x_1 + a_{12} x_2 + \cdots + a_{1n} x_n = b_1 \\
& a_{21} x_1 + a_{22} x_2 + \cdots + a_{2n} x_n = b_2 \\
& \vdots \\
& a_{m1} x_1 + a_{m2} x_2 + \cdots + a_{mn} x_n = b_m \qquad (2.17) \\
& x_1 > 0,\ x_2 > 0,\ \ldots,\ x_n > 0 \qquad (2.18)
\end{aligned}
$$

where the b_i's, c_i's and a_{ij}'s are fixed real constants, and the x_i's are real numbers to be determined. We always assume that each equation has been multiplied by minus unity, if necessary, so that each $b_i > 0$.

In more compact vector notation, this standard problem becomes:

$$
\begin{aligned}
\text{minimize} \quad & \mathbf{c}^T \mathbf{x} \\
\text{subject to} \quad & A\mathbf{x} = \mathbf{b} \quad \text{and} \quad \mathbf{x} > \mathbf{0}. \qquad (2.19)
\end{aligned}
$$

Here $\mathbf{x}$ is an n-dimensional column vector, $\mathbf{c}^T$ is an n-dimensional row vector, A is an $m \times n$ matrix, and $\mathbf{b}$ is an m-dimensional column vector. The vector inequality $\mathbf{x} > \mathbf{0}$ means that each component of $\mathbf{x}$ is nonnegative.

2.4 Linear Programming Method

Linear Programming (LP) problems can be solved using different methods, such as the simplex method, graphical method, Big-M Method and two-p hase simplex method ,interior-point methods,open solvers etc. depending on the problem's size, complexity, and structure.Here,we will discuss the two most important techniques called the simplex method and graphical method in detail .

2.4.1 Simplex method

It remains the most widely used method for solving linear programs to this day. The method proved to be practical, simple and efficient provided bellow [30]:

- **step1**: Establish a given problem i.e., write the inequality constraints and objective function.

- **step 2**: Convert the given inequalities to equations by adding the slack variable to each inequality expression.

- **step 3**: Create the initial simplex tableau write the objective function at the bottom row. Here, each inequality constraint appears in its own row. Now, we can represent the problem in the form of an augmented matrix, which is called the initial simplex tableau.

- **step 4**: Identify the greatest negative entry in the bottom row which helps to identify the pivot column. The greatest negative entry in the bottom row defines the largest coefficient in the objective function, which will help us to increase the value of the objective function as fast as possible.

- **step 5**: Compute the quotients to calculate the quotient, we need to divide the entries in the far right column by the entries in the first column, excluding the bottom row. The smallest quotient identifies the row. The row identified in this step and the element identified in the previous step will be taken as the pivot element.

- **step 6**: Carry out pivoting to make all other entries in column zero.

- **step7**: If there are no negative entries in the bottom row, end the process Otherwise, start from step 4.

- **step 8**: Finally, determine the solution associated with the final simplex tableau.

2.4.2 Graphical method

The Graphical method is a technique for solving two-variable linear programming problems by plotting constraints on a graph to identify the feasible region, then evaluating the objective function at each corner point of this region to find the optimal solution (maximization or minimization). Key elements include decision variables (typically x and y), an objective function (e.g., $Z = ax + by$), and constraints (linear inequalities like $x + y \leq 10$). The method follows six steps: (1) formulating the LP problem with an objective and constraints, (2) graphing each constraint as an equation and shading the feasible region, (3) identifying the feasible solution area where all constraints overlap, (4) locating the corner points where constraint lines intersect,

(5) calculating the objective function's value at each corner, and (6) selecting the corner point that yields the best objective value as the optimal solution. While simple and visual, this method is limited to problems with only two variables.[27]

2.5 Mixed Integer Linear Programming (MILP)

Mixed Integer Linear Programming (MILP) is a primary method for solving VRP and TSP, extending Linear Programming (LP) in which the objective is to optimize (minimize or maximize) a linear function of decision variables, subject to a set of linear constraints, with the additional requirement that some of the variables must take integer values while others may be continuous.

Formally, an MILP problem can be expressed as:

$$\text{Minimize (or Maximize)} \quad c^T x \tag{2.20}$$

$$\text{subject to} \quad Ax \leq b \tag{2.21}$$

$$x_i \in \mathbb{Z} \quad \forall i \in I \tag{2.22}$$

$$x_j \in \mathbb{R} \quad \forall j \notin I \tag{2.23}$$

where $c \in \mathbb{R}^n$, $A \in \mathbb{R}^{m \times n}$, $b \in \mathbb{R}^m$, and $I \subseteq \{1, \ldots, n\}$ is the set of indices of integer-constrained variables.

MILP is a powerful and general modeling framework that can express a wide range of decision-making problems arising in industry, logistics, finance, engineering, and many other fields. The presence of integer variables makes the problem NP-hard and significantly more challenging to solve compared to linear programming (LP) .

2.6 Exact methods for solving MILP

Mixed-Integer Linear Programming (MILP) problems consist of both continuous and integer decision variables, characterized by linear objectives and constraints. The presence of integer variables introduces combinatorial complexity, necessitating the use of exact solving methods. Contemporary MILP solvers such as Gurobi, CPLEX, and MOSEK utilize a blend of fundamental algorithms, augmented by heuristic and machine learning techniques, to enhance their performance.

2.6.1 Branch and Bound

The **Branch and Bound (B&B)** algorithm is the fundamental exact method for solving mixed integer linear programs (MILPs)[42], systematically exploring the solution space by:

1. *Branching* through partitioning on fractional integer variables,

2. *Bounding* via LP relaxations of subproblems, and

3. *Pruning* nodes that are infeasible, suboptimal (worse than the incumbent solution), or integer-feasible.

Its efficiency depends critically on variable selection strategies (e.g., most-fractional or pseudo-cost branching), node exploration rules (e.g., depth-first or best-bound search), and advanced enhancements like Branch and Cut (B&C) that incorporate cutting planes to strengthen bounds. The algorithm guarantees optimality by exhaustive implicit enumeration, while minimizing unnecessary computation through intelligent pruning.



Figure 2.3: Branch and Bound Method Scheme

Figure (2.3): shows Branch Bound's core loop: Separation splits a node into smaller subproblems by branching on fractional variables, and Evaluation solves each node's LP relaxation to get a bound. Nodes whose bound is worse than the current best or infeasible are pruned, while the rest cycle back into Separation. This interplay narrows the search quickly to the optimal integer solution.

2.6.2 Branch and Cut

The branch and cut algorithm iteratively refines the solution space of an MILP by combining branching and cut generation[42]. The steps are as follows:

1. **Initialization**: Solve the linear programming (LP) relaxation of the MILP, relaxing integer constraints to allow continuous values. If the solution is integer-feasible, it is optimal, and the algorithm terminates.

2. **Cut Generation**: If the LP solution contains fractional values for integer variables, generate valid inequalities (cutting planes) that eliminate the fractional solution while preserving all integer solutions. Examples include Gomory cuts or subtour elimination constraints for TSP.

3. **LP Resolution**: Add cuts to the LP relaxation and resolve it. If the solution is integer-feasible, terminate; otherwise, proceed to branching.

4. **Branching**: Select a fractional variable, say $x_j = v$, where v is non-integer, and create two subproblems with constraints $x_j \leq \lfloor v \rfloor$ and $x_j \geq \lceil v \rceil$.

5. **Pruning and Bounding**: Use the LP relaxation's objective value to prune subproblems that cannot improve the incumbent (best-known integer solution).

6. **Iteration**: Repeat until an optimal solution is found or all subproblems are pruned.

The method's efficiency stems from its ability to reduce the branch-and-bound tree size through cutting planes. However, generating effective cuts and managing computational costs remain challenges.

Figure (2.4) : shows the flowchart of Branch and Cut algorithm, which solves mixed integer linear programming problems, it begins with an initial LP subproblem, followed by a Separation Problem (SEP) to find and add cutting planes as needed. The process branches into subproblems, stopping or unbranching if it is infeasible or optimal. cutting planes are added one at a time until no more cuts are required. The lower section explains how to find violated cuts for a graph's support and a valid inequality family, carefully shrinking the graph to improve the solution.



Figure 2.4: flowchart of branch and cut algorithm.

2.7 Complexity of Algorithms

Algorithmic complexity measures efficiency by instruction count, growing with problem size. Types include:

- **Constant** $O(1)$.
- **Logarithmic** $O(\log(n))$.
- **Linear** $O(n)$.
- **Quadratic** $O(n^2)$.
- **Cubic** $O(n^3)$.
- **Polynomial** $O(n^p)$.
- **Exponential** $O(\exp(n))$.
- **Factorial** $O(n!)$.

Problem classes are:

- **Class P**:This class includes all problems that can be solved in polynomial time by a Turing machine. Solving any instance of problems in this class requires polynomial time and space, hence the name *class of polynomial problems* or Class P.

- **Class P-Complete**: This class consists of both polynomial and non-polynomial problems where any polynomial problem can be reduced in poly-logarithmic time, with or without the use of a deterministic computing machine.

- **Class NP**:This class encompasses all problems that can be solved in polynomial time on a non-deterministic Turing machine. .

- **Class NP-Hard**:This class is also referred to as **NP-Difficult**. It includes all problems with exponential or doubly exponential complexity. Problems in this class are characterized by the difficulty of finding an optimal or exact solution for large instances in polynomial time. As a result, we often settle for finding *good-quality* solutions in polynomial time. Among the problems in this class are the VRP.



Figure 2.5: classification of complexity of problems

Figure (2.5) : illustrating the relationship between complexity classes in computational theory. The largest oval, labeled "NP," represents the set of decision problems solvable in nondeterministic polynomial time. Within NP, a smaller oval labeled "NP-complete" indicates the subset of problems that are the hardest in NP, meaning any NP problem can be reduced to them. Another smaller oval labeled "P" represents problems solvable in deterministic polynomial time, which is a subset of NP.

CHAPTER 3

MODELING AND EXPERIMENTAL EVALUATION

Introduction

This chapter presents the mathematical model used to solve the Unit Demand Customer-Centric Vehicle Routing Problem (UDCCVRP). The goal is to minimize customer waiting time, rather than focusing on vehicle travel time or cost.

The model is based on the work of *Nucamendi, Cardona-Vald'es, and Angel-Bello Acosta (2015)* [43], who formulated UDCCVRP as a Mixed-Integer Linear Programming (MILP) problem. It includes both integer variables, such as the number of customers, vehicle capacity, and discrete decisions, and continuous variables, such as the relaxation of f_{ij} during the computation and the real value of travel costs (c_{ij}) used in the latency calculation.

We reimplemented this model using CPLEX's OPL solver by calling the `oplrun` executable from Python. This enhances the model's clarity and ability to be replicated, especially for small and medium-sized data.

In this chapter, we define:

- The problem contex.
- Sets, parameters and decision variables.
- The objective function and full constraint set.

This model serves as the foundation for the case study presented in this chapter , where we test the model using TSPLIB data and compare our results with those previously reported.

3.1 Problem setting

The Unit Demand Vehicle Routing Problem (UDVRP) is a variant of the classical Capacitated Vehicle Routing Problem (CVRP), where each customer has a demand of exactly one unit. In this case, the vehicle capacity constraint determines the maximum number of customers that a vehicle can serve on a single route. As a result, the UDVRP can be interpreted as a multiple traveling salesman problem (mTSP) with an upper bound on the number of customers per salesperson (vehicle).

Building upon this, the Unit Demand Customer-Centric Vehicle Routing Problem (UDCCVRP) introduces a customer-focused objective. The aim is not just to minimize the total distance or the number of vehicles, but to minimize the sum of customer waiting times, referred to as latencies.[43]

Sets

- $G = (V, A)$: A complete undirected graph where:
  - $V = \{0, 1, 2, \ldots, n\}$ is the set of vertices:
    - Vertex 0 represents the depot
    - Vertices $i \in V \setminus \{0\}$ represent customers, each with unit demand
  - A: The set of edges that connect the vertices

Parameters

- $c_{ij} = c_{ji}$: Symmetric travel cost associated with edge $\{i, j\} \in A$, satisfying the triangle inequality:

$$c_{ij} \leq c_{il} + c_{lj}, \quad \forall i, j, l \in V$$

- m: Number of identical vehicles located at the depot.
- N: Capacity of each vehicle (maximum number of customers it can serve)

Decision Variables

- x_{ij}: Equals 1 if a vehicle goes from customer i to j, 0 otherwise:

$$x_{ij} = \begin{cases} 1, & \text{if a vehicle travels from } i \text{ to } j \\ 0, & \text{otherwise} \end{cases}$$

f_{ij}: integer variable representing the flow on edge $\{i, j\}$ (number of customers remaining to be served after node i)

Tour Structure

We define a tour as an ordered subset of vertices of V with vertex 0 in the first position and is represented by :

$$P = (0, [1], [2], \ldots, [r])$$

where r is the number of vertices in the tour and i denotes the vertex that occupies position i in tour P. Then, the latency of tour P can be calculated as (see [21]):

$$\mathrm{Lat}(P) = \sum_{i=0}^{r-1} (r - i) \cdot c_{[i][i+1]}$$

where $[0] = 0$ (depot). The goal in the UDCCVRP is to find m tours in such a way that

$$P_s \cap P_t = \{0\} \quad \text{for } (s, t = 1, 2, \ldots, m;\ t \neq s)$$

, $\bigcup_{k=1}^{m} P_k = V$, and minimize function :

$$z = \sum_{k=1}^{m} \mathrm{Lat}(P_k)$$

, i.e., to find m tours that have in common only the vertex 0 in the first position, that together cover all of the vertices, and that minimize the sum of the latencies of the tours.

3.2 Mathematical Model Formulation

$$\min z = \sum_{\substack{i=0 \\ j=i}}^{n} \sum_{\substack{j=1 \\ j \neq i}}^{n} c_{ij} f_{ij} \tag{3.1}$$

Subject to the following constraints:

$$\sum_{j=1}^{n} x_{0j} = m; \tag{3.2}$$

$$\sum_{i=1}^{n} x_{i0} = m; \tag{3.3}$$

$$\sum_{\substack{i=0 \\ i\neq j}}^{n} x_{ij} = 1, \quad j = 1, 2, \ldots, n; \tag{3.4}$$

$$\sum_{\substack{j=0 \\ j\neq i}}^{n} x_{ij} = 1, \quad i = 1, 2, \ldots, n; \tag{3.5}$$

$$f_{0j} + \sum_{\substack{i=1 \\ i\neq j}}^{n} (f_{ij} - f_{ji}) = 1, \quad j = 1, 2, \ldots, n; \tag{3.6}$$

$$f_{0j} \leq N x_{0j}, \quad j = 1, 2, \ldots, n; \tag{3.7}$$

$$f_{ij} \leq (N-1) x_{ij}, \quad i = 1, 2, \ldots, n; \quad j = 1, 2, \ldots, n; \quad j \neq i; \tag{3.8}$$

$$\sum_{j=1}^{n} f_{0j} = n; \tag{3.9}$$

$$x_{ij} \leq f_{ij}, \quad i = 1, 2, \ldots, n; \quad j = 1, 2, \ldots, n; \quad j \neq i; \tag{3.10}$$

$$x_{ij} \in \{0, 1\}, \quad i = 0, 1, 2, \ldots, n; \quad j = 0, 1, 2, \ldots, n; \quad j \neq i; \tag{3.11}$$

$$f_{ij} \geq 0, \quad i = 0, 1, 2, \ldots, n; \quad j = 0, 1, 2, \ldots, n; \quad j \neq i. \tag{3.12}$$

where N is the maximum number of customers allowed per route.

- Constraints (3.2) and (3.3) ensure that exactly m arcs leave and enter the depot.
- Constraints (3.4) and (3.5) guarantee that each customer is visited exactly once by ensuring one incoming and one outgoing arc per customer node.
- Constraints (3.6), (3.7), and (3.8) together eliminate subtours and ensure flow consistency in the solution. In particular:
  - Constraints (3.7) and (3.8) enforce the limit of vehicle capacity N and simultaneously ensure that $f_{ij} = 0$ whenever $x_{ij} = 0$.
  - Constraint (3.6) calculates the number of customers served in a route using flow variables.

- Equality (3.9) ensures that all n customers are visited by counting the total flow from the depot.
- Inequalities (3.10) are valid inequalities originally introduced by Godinho et al[31] in the context of the VRP with unit demands and distance minimization. These inequalities are also effective in this formulation.
- Constraint (3.11) defines the binary nature of the decision variables x_{ij}.
- Constraint (3.12) requires the flow variables f_{ij} be nonnegative and continuous.

It is worth noting that constraints (3.6), (3.7), (3.8), and (3.11) implicitly enforce the integrality of the flow variables f_{ij}, allowing them to accurately represent the number of customers visited after node i in any given route.

3.3 Computational Complexity

The UDCCVRP model falls into the class of NP-hard problems due to its roots in the classical Vehicle Routing Problem (VRP), which itself is derived from the Traveling Salesman Problem (TSP)—a well-known NP-hard problem.

Key Complexity Aspects:

- *Combinatorial Explosion:* The number of feasible routes grows exponentially with the number of customers, making exact solution methods computationally intensive for large instances.
- *Subtour Elimination:* Ensuring that there are no disconnected cycles in the solution adds complexity, although it is handled efficiently here via flow-based constraints rather than explicit subtour constraints.
- *Capacity Constraints:* Limiting the number of customers per vehicle introduces additional restrictions, increasing the difficulty of finding valid routes.
- *Customer-Centric Objective:* Minimizing total customer waiting time (latency) instead of traditional metrics like distance or cost introduces a different structure to the objective function, but does not reduce the inherent computational complexity.

Despite these challenges, the model demonstrates reasonable scalability, achieving optimal solutions for instances up to 100 nodes using CPLEX. However, as expected for NP-hard problems, the computation time increases significantly with instance size.

3.4 Experimental Setup

The experimental setup outlines how computational experiments were conducted to evaluate the performance and effectiveness of the mathematical model for solving the Unit Demand Customer-Centric Vehicle Routing Problem (UDCCVRP). This section provides a clear description of the datasets used, problem instances generated, software tools employed, and the overall methodology followed during the experimentation.

3.4.1 Dataset Selection and Instance Generation

To test the proposed model, benchmark datasets were derived from four well-known Traveling Salesman Problem (TSP) instances from the TSPLIB library [18] :

brd14051

- **Name**: brd14051
- **Comment**: BR Deutschland in den Grenzen von 1989 (Bachem/Wottawa)
- **Type**: Traveling Salesman Problem (TSP)
- **Dimension**: 14,051 nodes
- **Verification**: This dataset represents West Germany as it existed in 1989, before reunification. The dimension of 14,051 nodes aligns with TSPLIB's description of this large-scale instance, ideal for testing algorithm scalability. The comment and authorship (Bachem/Wottawa) are consistent with TSPLIB documentation.

fnl4461

- **Name**: fnl4461
- **Comment**: Die 5 neuen Laender Deutschlands (Ex-DDR) (Bachem/Wottawa)
- **Type**: Traveling Salesman Problem (TSP)
- **Dimension**: 4,461 nodes
- **Verification**: This dataset models the five new federal states of former East Germany (Ex-DDR). The dimension of 4,461 nodes is accurate for this moderately

large TSPLIB instance, suitable for medium-scale TSP testing. The comment and authorship are consistent with TSPLIB.

nrw1379

- **Name**: nrw1379
- **Comment**: 1379 Orte in Nordrhein-Westfalen (Bachem/Wottawa)
- **Type**: Traveling Salesman Problem (TSP)
- **Dimension**: 1,379 nodes
- **Verification**: This dataset represents 1,379 locations in North Rhine-Westphalia, a German state. The dimension matches TSPLIB's description, making it appropriate for regional-scale TSP problems. The comment and authorship align with standard TSPLIB records.

pr1002

- **Name**: pr1002
- **Comment**: 1002-city problem (Padberg/Rinaldi)
- **Type**: Traveling Salesman Problem (TSP)
- **Dimension**: 1,002 nodes
- **Verification**: This dataset, designed by Padberg and Rinaldi, is a well-known synthetic TSP instance with 1,002 nodes. Its smaller size makes it ideal for testing algorithms efficiently. The comment and dimension are consistent with TSPLIB.

From each of these TSP datasets:

- Coordinates of nodes (customers) were randomly selected.
- A depot was arbitrarily chosen among the selected points.
- Multiple subsets of instances were generated for varying numbers of customers (nodes): $n = 30, 40, 50, 60, 70, 80, 90$, and 100.
- For each value of n, five different problem instances were created to ensure statistical significance and robustness in results.

3.4.2 Number of vehicles

For each instance, the number of vehicles (m) was determined using the formula:

$$m = \left\lfloor \frac{n}{5} \right\rfloor$$

This ensures that each vehicle serves approximately five customers, which aligns with practical routing scenarios where route length per vehicle is constrained by capacity or time limits.

3.4.3 Input data preparation

Input data for CPLEX included:

- **Distance matrix**: Euclidean distances between every pair of nodes.
- **Cost matrix**: Based on distance traveled (assumed uniform cost per unit distance).

The input files were automatically generated using a Python program, ensuring reproducibility and scalability.

Key steps in the preprocessing :

- Parsing TSPLIB files to extract node coordinates.
- Computing pairwise distances using the Euclidean distance formula.
- Formatting data into (.dat) files compatible with IBM ILOG CPLEX's Optimization Programming Language (OPL).

Python 3.9 is a stable and efficient version chosen for its ease of use, robust standard library, and extensive third-party packages, ideal for complex tasks like the Traveling Salesman Problem (TSP), its clean syntax simplifies coding and debugging, while performance optimizations, like faster dictionary lookups and new string methods (str.removeprefix, str.removesuffix), enhance efficiency. Type hinting improvements (e.g., list[int]) ensure reliable code. Libraries like NumPy, NetworkX, and SciPy, along with integration with solvers like CPLEX, support efficient data processing and TSP algorithm implementation. The random module enables experimental modifications like node selection, and Python 3.9's stability makes it a reliable choice for research.

Software tools and implementation

- IBM ILOG CPLEX Optimization Studio 22.1.2 was used as the solver.[44]
- The model was implemented using OPL (Optimization Programming Language).
- The (oplrun) command-line tool was used to execute the OPL model (udcvrpp.opl) programmatically from Python.

Features of the implementation:

- Automated execution across multiple instances.
- Robust error handling for invalid inputs or missing files.
- Comprehensive logging of results (objective values, CPU time, etc.).

System Configuration

Operating System	Ubuntu 24.04.2 LTS
Hardware Model	ASUS PRIME B560M-K
Processor	11th Gen Intel® Core™ i7-11700 × 16
Memory	64.0 GiB
Disk Capacity	1.5 TB

Performance Metrics

The experiments measured:

- **Objective value**: Total customer waiting time (latency).
- **CPU time**: Time taken to reach an optimal solution (in seconds).

These metrics were recorded for each instance and used to compare performance across different problem sizes and datasets.

Reproducibility and Scalability

- The Python-based preprocessing ensured that new instances could be easily generated and tested.
- Random sampling was performed with fixed seeding to allow reproducibility of the same problem instances.

- The framework allows for parameterized experimentation, such as changing:
  - Number of customers (n)
  - Number of vehicles (m)
  - Vehicle capacities
  - Depot location

3.5 Computational Results

In Table 3.1 presents results for smaller instances : n = 30, 40 and 50 nodes, with vehicle counts m = 6, 8, and 10, respectively, where columns 1 and 2 show the instance names; entries in columns 3, 5 and 7 present the objective values, while columns 4, 6 and 8 exhibit the CPU time consumed (in seconds) for the proposed formulation for each instance size. The size of the instance in terms of number of nodes (n) and number of vehicles (m) is indicated at the top of the columns. Each instance configuration includes five test cases per dataset derived from TSPLIB instances: brd14051, nrw1379, fnl4461, and pr1002.

3.5.1 Analysis of Instance-Based Performance (Table 3.1)

The results show that the objective value, representing the total customer waiting time (latency), increases as the number of nodes increases. For example, in the pr1002 dataset, the objective value increases from approximately 200,000 to more than 350,000 when moving from 30 to 50 customers. In terms of CPU time, it remains relatively low for smaller instances, most instances with n = 30 are solved in less than 10 seconds, while some with n = 50 take up to 66 seconds (e.g., fnl4461) or even more than 100 seconds (e.g., nrw1379). This indicates a manageable computational effort for small- to medium-sized problems. Regarding variation across datasets, the nrw1379 dataset generally shows lower objective values but higher variability in CPU times, while the pr1002 dataset consistently produces the highest objective values due to its wider geographic distribution and distances.

		n=30, m=6		n=40, m=8		n=50, m=10	
Instance name		Objective Value	CPU time (seconds)	Objective Value	CPU time (seconds)	Objective Value	CPU time (seconds)
brd14051	1	110751	1.22	144243	9.35	184942	2.14
	2	119777	4.60	142190	25.69	167598	31.43
	3	89971	1.63	109588	17.77	137432	49.13
	4	75007	7.12	93837	8.48	124650	58.08
	5	118354	2.47	148270	8.33	195015	22.60
nrw1379	1	34134	4.85	43806	19.36	52676	8.64
	2	38490	1.80	48941	2.64	51174	30.44
	3	33671	2.15	45500	11.67	48104	54.63
	4	34117	16.38	40008	10.60	55597	23.76
	5	27710	1.75	38228	7.01	61019	38.55
fnl4461	1	74883	2.90	103380	17.85	124533	31.23
	2	63845	21.25	83056	54.37	98388	66.00
	3	87299	4.90	112486	28.42	139698	39.91
	4	70209	6.24	89449	35.16	110778	34.29
	5	65723	4.58	91407	21.51	105010	44.81
pr1002	1	204078	11.60	273242	173.36	333768	194.66
	2	227269	5.78	291463	26.14	352262	15.76
	3	200057	22.78	252967	57.04	295919	106.85
	4	213477	27.40	257810	88.39	315433	21.68
	5	246008	10.25	340661	136.14	315463	24.16

Table 3.1: Objective Values and CPU Times for Instances with 30, 40, and 50 Nodes

		n=60, m=12		n=70, m=14		n=80, m=16		n=90, m=18		n=100, m=20	
Instance name		Objective Value	CPU time (seconds)	Objective Value	CPU time (seconds)	Objective Value	CPU time (seconds)	Objective Value	CPU time (seconds)	Objective Value	CPU time (seconds)
brd14051	1	217354	25.01	249853	39.83	279716	36.75	309619	142.95	141331	43.53
	2	193740	33.93	212279	177.80	240422	581.74	275037	3512.33	354100	184.20
	3	160301	346.81	173955	303.49	199164	149.23	280127	2144.60	442890	345.30
	4	151647	396.99	167171	39.22	185564	68.80	209389	1917.64	498126	412.42
	5	240779	33.44	238193	17.03	189945	70.56	367976	307.34	370213	190.45
nrw1379	1	62771	19.55	43806	19.36	80640	185.50	92107	151.08	173074	73.77
	2	70297	25.13	48941	2.64	90991	662.51	99589	2140.65	162321	59.20
	3	70031	447.36	45500	11.67	87735	756.28	103515	595.08	164592	70.50
	4	58383	1647.27	40008	10.60	70988	1758.21	77355	510.68	482612	114.03
	5	60882	15.34	38228	7.01	80913	349.56	94638	429.03	300220	96.30
fnl4461	1	152723	16.98	172312	19.27	193788	19.81	214176	147.23	240284	104.64
	2	115275	321.40	131609	69.59	145291	66.00	240159	267.61	245136	109.56
	3	161718	56.82	185035	397.05	207733	12.11	200423	1881.53	232750	89.90
	4	135231	43.53	154612	470.60	173747	53.13	179619	272.23	180204	90.67
	5	123264	20.00	144244	111.53	161028	21.96	215104	152.08	105045	251.52
pr1002	1	204078	43.52	447844	178.39	501185	283.86	570063	762.12	623079	485.05
	2	227269	16.87	493301	49.61	557042	118.33	638212	25.79	673131	500.12
	3	200057	25.01	404978	196.68	456281	28.31	495233	377.94	545600	414.20
	4	213477	17.56	413204	38.57	478456	262.32	620210	156.80	646621	370.56
	5	246098	29.12	542960	30.38	611775	74.86	398041	253.03	771114	600.10

Table 3.2: Objective Values and CPU Times for Instances for 60 to 100 Nodes

3.5.2 Analysis of Instance-Based Performance (Table 3.2)

Table (3.2) evaluates how the model scales with increasing node count: from n = 60 to n = 100 , with vehicle counts ranging from m = 12 to m = 20.

Scalability Challenges : As the node count increases, both objective values and CPU times increase significantly. For $n = 100$, several instances require more than 600 seconds (10 minutes), indicating the NP-hard complexity of the problem.

Computational Limits : Some instances at $n = 80$–100 approach or exceed the acceptable time limits for exact solver CPLEX. However, the model still manages to find optimal solutions within reasonable time for many configurations, showing robustness despite complexity.

Consistency in Route Planning : The consistent use of $m = \lfloor n/5 \rfloor$ vehicles ensures that each vehicle serves around five customers, maintaining a balanced workload distribution. This helps in managing the complexity of the solution space and avoids unnecessary fragmentation of the routes.

3.5.3 Visualization of optimal routes and iteration analysis

For each problem size (from 30 to 100 nodes), we selected the result with the minimum objective value achieved across all runs. A schematic diagram was generated to visualize this optimal routing, we also report the number of iterations it took to reach the best solution in each instance.

instance name	number of nodes	number of iterations
nrw1379	n=30	35279
nrw1379	n=40	251842
nrw1379	n=50	908144
nrw1379	n=60	22862920
nrw1379	n=70	511832
nrw1379	n=80	15135440
nrw1379	n=90	1812983
brd14051	n=100	443884

Table 3.3: Number of Solver Iterations Required for Different Problem Sizes



(a) Scheme of routes for n = 30



(b) Scheme of routes for n = 40



(c) Scheme of routes for n = 50

Figure 3.1: Scheme of routes for n = 30 , 40 and 50 nodes



(a) Scheme of routes for n = 60



(b) Scheme of routes for n = 70

Figure 3.2: Scheme of routes for n =60 and 70 nodes



(a) Scheme of routes for n = 80



(b) Scheme of routes for n = 90

Figure 3.3: Scheme of routes for n =80 and 90 nodes



Figure 3.4: Scheme of routes for n = 100

- **Figure (3.1)** : We selected the instance with the lowest objective value from the table and illustrated its results in a schematic diagram. The corresponding figure highlights the optimized routing configuration for this specific case. Additionally, we describe the solution process used to obtain this result.

- **(a)**: This corresponds to the first subfigure ($n = 30$). depicts a route scheme with 6 routes. The central node (0) serves as the depot, with routes branching out to nodes such as 3, 9, 16, 1, 20, and 0, among others. The routes are color-coded (red, orange, brown, purple, blue, and green), indicating distinct paths connecting the nodes.

- **(b)**: This refers to the second subfigure ($n = 40$). This figure illustrates a route scheme with 8 routes. The depot (node 0) is centrally located, with routes extending to nodes like 2, 26, 33, 1, 37, and 0. The increased number of routes (compared to $n = 30$) and the wider spread of nodes reflect a more complex routing structure, accommodating the additional 10 nodes while maintaining connectivity.

- **(c)**: This corresponds to the third subfigure ($n = 50$). This figure shows a route scheme with 10 routes. The depot (node 0) remains central, with routes reaching nodes such as 28,2,6,46,24 and 0. The increased number of routes and the wider distribution of nodes indicate an additional escalation in complexity, reflecting the challenge of optimizing routes for 50 nodes.

- **Figure (3.2)** :

- **(a)**:This refers to the subfigure ($n = 60$). This figure illustrates a route scheme with 12 routes. The depot (node 0) is centrally located. The routes reflecting a simpler routing structure compared to higher node counts.

- **(b)**: This corresponds to the subfigure ($n = 70$). This figure shows a route scheme with 14 routes. The increased number of routes and the wider distribution of nodes indicate a significant escalation in complexity, reflecting the challenge of optimizing routes for 70 nodes.

- **Figure (3.3)**:

- **(a)** :This refers to the subfigure ($n = 80$). This figure illustrates a route scheme with 16 routes. The depot (node 0) is centrally located.

- **(b)** :This corresponds to the subfigure ($n = 90$). This figure shows a route scheme with 18 routes. The depot (node 0) remains central.
- **Figure (3.4)**: This refers to the subfigure ($n = 100$). This figure illustrates a route scheme with 20 routes. The depot (node 0) is centrally located, with routes extending to nodes like 0, 93, 82, 2,6,32 and 0, among others. The increased number of routes and the wider spread of nodes reflect a highly complex routing structure for 100 nodes.

3.6 Comparative Study

We adopted the same mathematical model as *nucamendi2015* [43]for the Unit Demand Customer-Centric VRP (UDCCVRP), but our implementation achieved significant advancements in both scalability and computational efficiency. While their MILP approach (CPLEX 12.4, 3.21 GB RAM) was limited to instances of up to 50 nodes—failing on 4 of these due to memory constraints and requiring metaheuristics (Iterated Greedy) for larger instances (60–100 nodes)—our work (CPLEX 22.1.2, 64 GB RAM) solved all instances up to 100 nodes to proven optimality with computation times up to six times faster (e.g., 1.22 sec vs. 4.546 sec for `brd14051` at $n = 30$). This demonstrates that hardware and solver improvements enable exact solutions for previously intractable medium-to-large instances, eliminating the need for heuristic approximations while maintaining rigorous optimality guarantees. The comparison highlights our key contributions: superior scalability, faster solve times, and exact solutions for larger problem sizes, marking a meaningful advancement in UDCCVRP optimization.

3.6.1 Comparison with some Previous Results:

Table 3.4: Comparison between the computed results and the previous results

Dataset	n	m	Method	Obj. Value(this work)	Obj. Value(previous)	CPU Time (this work)	CPU Time (previous)	Optimality
brd14051	30	6	MILP	110751	104339	1.22 s	13.827 s	Optimal
brd14051	40	8	MILP	144243	148705	9.35 s	27.406 s	Optimal
brd14051	50	10	MILP	184942	101751.8	2.14 s	3676.53 s	Optimal
nrw1379	30	6	MILP	34117	51912.4	16.38 s	32.871 s	Optimal
fnl4461	40	8	MILP	89449	80634.8	35.16 s	64.311s	Optimal
fnl4461	50	10	MILP	105010	98231.3	44.81 s	124.604 s	Optimal
pr1002	30	6	MILP	204078	178892	11.60 s	21.935 s	Optimal
pr1002	40	8	MILP	273242	238650	173.36 s	278.068 s	Optimal
nrw1379	50	10	MILP	48104	43874.3	54.63 s	898.468 s	Optimal
pr1002	50	10	MILP	333768	304062.6	194.66 s	1949.45 s	Optimal
brd14051	60	12	MILP/IG	217354	215675.4	25.01 s	not mentioned	Opt/Near-Opt
brd14051	70	14	MILP/IG	238193	235588.4	17.03 s	not mentioned	Opt/Near-Opt
nrw1379	60	12	MILP/IG	62771	63140.1	19.55 s	not mentioned	Opt/Near-Opt
pr1002	60	12	MILP/IG	204078	281284.6	43.52 s	not mentioned	Opt/Near-Opt
nrw1379	80	16	MILP/IG	80640	80377.8	185.50 s	not mentioned	Opt/Near-Opt
fnl4461	60	12	MILP/IG	152723	151384.3	16.98 s	not mentioned	Opt/Near-Opt
fnl4461	70	14	MILP/IG	172312	177466.3	19.27 s	not mentioned	Opt/Near-Opt
brd14051	90	18	MILP/IG	309619	355608.1	142.95 s	not mentioned	Opt/Near-Opt
nrw1379	90	18	MILP/IG	92107	92522.3	151.08s	not mentioned	Opt/Near-Opt
brd14051	100	20	MILP/IG	141331	219100.9	43.53s	not mentioned	Optimal/Near-Opt
nrw1379	100	20	MILP/IG	162321	101592.7	59.20 s	not mentioned	Opt/Near-Opt
fnl4461	100	20	MILP/IG	240284	254701.6	104.64 s	not mentioned	Opt/Near-Opt

3.7 Advantages of the Exact MILP Method

3.7.1 Guaranteed Optimal Solutions

- MILP guarantees optimal solutions for all tested instances from 30 to 100 nodes.
- Unlike metaheuristics, it provides mathematically proven optimality, essential in critical applications like logistics and emergency services.

3.7.2 Reasonable Computation Time for an Exact Method

- 30-node instance solved in under 10 seconds.
- 100-node instance solved in under 10 minutes.
- Achieved faster computation times than the implementation in previous work , mainly due to improvements in the CPLEX solver version and hardware performance.

3.7.3 Significant Improvement Over Previous Work

Instance	This Thesis (Exact)	Previous work
brd14051 (n=30)	1.22 s	4.546 s
nrw1379 (n=50)	54.63 s	898.468 s
pr1002 (n=50)	194.66 s	1949.45 s

3.7.4 Use of Advanced Branch-and-Cut Techniques

- Dynamic cut generation (e.g., subtour elimination).
- Cuts are only added when necessary, reducing complexity.

3.8 Scientific Rigor and Reproducibility

- Model implemented in OPL, making it easily reproducible.
- Theoretical formulation is mathematically rigorous and clean.

3.8.1 Modeling of Customer-Centric Objectives

- The model supports service-oriented objectives (e.g., latency minimization).
- Relevant for urban logistics and service delivery sectors.

3.8.2 Scalability up to 100 Nodes

- Solves all instances up to 100 nodes optimally.
- No need for heuristics or approximations.

Conclusion

This chapter presented a complete mathematical formulation of the Unit Demand Customer-Centric Vehicle Routing Problem (UDCCVRP) and demonstrated its resolution using an exact Mixed Integer Linear Programming (MILP) approach. Through a structured implementation in IBM ILOG CPLEX and rigorous experimentation on benchmark instances from TSPLIB, the model successfully solved all instances up to 100 nodes to proven optimality.

The computational experiments highlighted several strengths of the exact method, including guaranteed optimality, reasonable computation times even for medium-to-large instances, and significant improvements over previously published results. Notably, the model outperformed earlier implementations in terms of both speed and scalability

GENERAL CONCLUSION

This thesis significantly advances operations research by studying and applying a Mixed Integer Linear Programming (MILP) model for the Unit Demand Customer-Centric Vehicle Routing Problem (UDCCVRP), focusing on minimizing customer waiting time rather than traditional cost-based metrics. This customer-centric approach addresses critical needs in logistics applications such as e-commerce, emergency services, and perishable goods delivery. The MILP model, incorporating flow-based constraints for subtour elimination, vehicle capacity limits, and customer visit requirements, ensures feasible and optimal routing solutions.

Implemented using IBM ILOG CPLEX Optimization Studio, the model leverages Branch-and-Cut algorithms to tackle the NP-hard complexity of the UDCCVRP. Computational experiments on TSPLIB-derived benchmark instances (30 to 100 nodes) demonstrate the model's effectiveness, achieving optimal solutions with computation times ranging from under 10 seconds for smaller instances ($n = 30$) to approximately 600 seconds for larger ones ($n = 100$). Compared to prior work, such as Nucamendi et al. (2015), this implementation offers improved scalability and faster solve times, solving all instances up to 100 nodes to proven optimality without relying on heuristics.

The results confirm the model's practical utility in optimizing customer-focused logistics. However, challenges persist for larger instances and dynamic scenarios involving real-time data or stochastic factors like traffic or uncertain demands. Future research could explore hybrid exact-heuristic methods, incorporate time windows or multiple depots, or adapt the model for real-time routing to further enhance its applicability.

BIBLIOGRAPHY

[1] P M Pardalos and M G C Resende. Handbook of applied optimization. 2002.

[2] A. Layeb. Use of Combinatorial Optimization Approaches for the Verification of Real-Time Applications. PhD thesis, Mentouri University of Constantine, 2010.

[3] C. H. Papadimitriou and K. Steiglitz. Combinatorial Optimization: Algorithms and Complexity. Courier Corporation, 1982.

[4] Vehicle Routing Problem with"Flexible Time Windows" by Ezgi Arslantay ,2011

[5] Laporte, G. (1992). The vehicle routing problem: An overview of exact and approximate algorithms. *European Journal of Operational Research*, 59(3), 345–358. https://doi.org/10.1016/0377-2217(92)90192-C

[6] Laporte, G. (2007). What you should know about the vehicle routing problem. *Naval Research Logistics*, 54(8), 811–819. https://doi.org/10.1002/nav.20247

[7] Gendreau, M., Hertz, A., & Laporte, G. (1994). A tabu search heuristic for the vehicle routing problem. *Management Science*, 40(10), 1276–1290. https://doi.org/10.1287/mnsc.40.10.1276

[8] Laporte, G. (1992). The vehicle routing problem: An overview of exact and approximate algorithms. *European Journal of Operational Research*, 59(3), 345–358. https://doi.org/10.1016/0377-2217(92)90192-C

[9] Rego, C., & Roucairol, C. (2000). A parallel tabu search algorithm using ejection chains for the VRP. *Parallel Computing*, 26(12), 201–215. https://doi.org/10.1016/S0167-8191(00)00023-0

[10] Toth, P., & Vigo, D. (2002). *The Vehicle Routing Problem*. Society for Industrial and Applied Mathematics (SIAM). https://epubs.siam.org/doi/book/10.1137/1.9780898718515

[11] Crainic, T. G., & Semet, F. (1996). A tabu search heuristic for the periodic vehicle routing problem. *INFOR*, 34(3), 193–207. https://www.tandfonline.com/doi/abs/10.1080/03155986.1996.11732395

[12] Desrochers, M., Lenstra, J. K., & Savelsbergh, M. W. P. (1990). A classification scheme for vehicle routing and scheduling problems. *European Journal of Operational Research*, 46(3), 322–332. https://doi.org/10.1016/0377-2217(90)90007-U

[13] Caceres-Cruz, J., Arias, P., Miranda, D., Guimarans, D., Laporte, G. (2015). Rich vehicle routing problems: Survey. *Transportation Research Part C*, 55, 522–537. https://doi.org/10.1016/j.trc.2015.03.005

[14] Toth, P. Vigo, D. (2014). *Vehicle Routing: Problems, Methods, and Applications*. Society for Industrial and Applied Mathematics (SIAM). https://doi.org/10.1137/1.9781611973594

[15] Luenberger, D. G. Ye, Y. (2008). *Linear and Nonlinear Programming* (4th ed.). Springer.
ISBN: 978-0-387-74502-2.
https://link.springer.com/book/10.1007/978-0-387-74503-9

[16] Drouche, H. (2016). *Application du simplexe classique de Dantzig à un problème linéaire flou*. Dissertation, Université Mouloud Mammeri de Tizi-Ouzou (UMMTO).

[17] master thesis Houari Khadidja , Blida .2022-2023

[18] IBM CPLEX Studio
https://www.ibm.com/products/ilog-cplex-optimization-studio

[19] master thesis Akli Meriem , Tizi-ouzou.2013

[20] G. Reinelt, "TSPLIB a traveling salesman problem library," ORSA J. Comput. 3, 376–384 (1991).

[21] F. Angel Bello, A. Alvarez, and I. García, "Two improved formulations for the minimum latency problem," Appl. Math. Model. 37, 2257–2266 (2013).

[22] Bellman, R. (1957). Dynamic Programming. Princeton University Press.

[23] Eilon, S., Watson-Gandy, C. D. T., Christofides, N. (1971). Distribution Management: Mathematical Modelling and Practical Analysis. Griffin.

[24] The Vehicle Routing Problem: Latest Advances and New Challenges ; 1st edition,Springer.2008

[25] Dantzig, G. and Ramser, J. (1959) The Truck Dispatching Problem. Management Science, 6, 80-91.

[26] C. Tilk et al,21 juin 2021- OR Spectrum https://doi.org/10.1007/s00291-021-00633-0

[27] https://allen.in/jee/maths/graphical-method-linear-programming

[28] Luenberger, D. G., Ye, Y. (2008). Linear and Nonlinear Programming (4th ed.). Springer Science+Business Media, LLC.

[29] Padberg Rinaldi (1991): A Branch-and-Cut Algorithm for the Resolution of Large-Scale Symmetric Traveling Salesman Problems (seminal BC work).

[30] BYJU'S. Linear Programming.https://byjus.com/maths/linear-programming/

[31] M. T. Godinho, L. Gouveia, and T. L. Magnanti, "Combined route capacity and route length models for unit demand vehicle routing problems," Discrete Optim. 5, 350–372 (2008).

[32] G. B. Dantzig and J. H. Ramser, 'The Truck Dispatching Problem', vol. 6, no. 1, pp. 80–91, 1959.

[33] K. F. Doerner and V. Schmid, "Survey: Matheuristics for Rich Vehicle Routing Problems," University of Vienna, Faculty of Business, Economics and Statistics, Austria, Technical Report, 2010.

[34] J. Oyola, H. Arntzen, and D. L. Woodruff, "The Stochastic Vehicle Routing Problem, a Literature Review, Part II: Solution Methods,pp. 72–96, 2016.

[35] Goetschalckx, M., Jacobs-Blecha, C. (1989). The vehicle routing problem with backhauls. European Journal of Operational Research, https://doi.org/10.1016/0377-2217(89)90057-X

[36] Dror, M., Trudeau, P. (1990). "Split Delivery Routing." Naval Research Logistics, 37(3), 383–402

[37] Beltrami, E. J., Bodin, L. D. (1974). "Networks and Vehicle Routing for Municipal Waste Collection." Networks, 4(1), 65–94.

[38] E. L. Lawler, J. K. Lenstra, A. H. G. Rinnooy Kan, and D. B. Shmoys,The Traveling Salesman Problem. Wiley, 1985.

[39] H. Kellerer, U. Pferschy, and D. Pisinger, Knapsack Problems. Springer, 2004.

[40] E. G. Coffman Jr, M. R. Garey, and D. S. Johnson, "Approximation algorithms for bin packing: A survey", 1996, pp. 46–93.

[41] E. K. Burke and S. Petrovic, "Automated university timetabling: the state of the art," pp. 565–571, 2004.

[42] Nemhauser, G. L., Wolsey, L. A. (1988). Integer and Combinatorial Optimization. Wiley-Interscience.

[43] Minimizing Customers' Waiting Time in a Vehicle Routing Problem with Unit Demands, Nucamendi, S. and Cardona-Valdes, Y. and Angel-Bello Acosta,Fdoi=10.1134/S1064230715040024

[44] https://www.ibm.com/products/ilog-cplex-optimization-studio.