

POWDER TECHNOLOGY

**AN INTERNATIONAL JOURNAL ON THE SCIENCE AND
TECHNOLOGY OF WET AND DRY PARTICULATE SYSTEMS**

EDITOR-IN-CHIEF

J.P.K. Seville (*Birmingham, UK*)

REGIONAL EDITORS

L.-S. Fan (*Columbus, OH, USA*)

M. Horio (*Tokyo, Japan*)

HONORARY EDITORS

R. Clift

J.C. Williams

Online Access Via:

www.elsevier.com/locate/powtec



(Contents continued from outside backover)

-The influence of the dispersion technique on the characteristics of the W-Cu powders and on the sintering behavior	123
F.A. da Costa, A.G.P. da Silva and U. Umbelino Gomes	
Free top fluidized bed surface fluctuations as a source of hydrodynamic data	133
J.V. Briongos and J.G. Soler	
Numerical simulation of mass transfer of a spherical particle assemblage with the cell model	145
Z.-S. Mao and Y. Wang	
Experimental determination of length-dependent saltation velocity in dilute flows	156
M. Hubert and H. Kalman	
Influence of particle shape on the packing and on the segregation of spherocylinders via Monte Carlo simulations	167
C.R.A. Abreu, F.W. Tavares and M. Castier	

- Colour and greyscale images should be supplied as TIFF or EPS files (resolution 300 dpi).
- Line drawings (black & white or colour) should be supplied as EPS files.

If you need help to create files in-house
www.elsevier.com/locate/authorartwork

Please also note:

- We still need a good quality hard copy of your figure in case the electronic file must match exactly.
- We can use floppy disks, ZIP disks or CD-ROM. Artwork files should be on a separate disk or CD to article text files.
www.elsevier.com/locate/authorartwork
- Only standard fonts should be used, for example: Times, Times New Roman, Helvetica, Arial, Symbol
www.elsevier.com/locate/authorartwork/formats
- Lines should be a minimum width of 0.5 pt.
www.elsevier.com/locate/authorartwork/lines
- Only standard colours should be used.
www.elsevier.com/locate/authorartwork/colours
- Lettering should be a consistent size and appropriate to the size of the figure.
www.elsevier.com/locate/authorartwork/sizing
- An image which looks acceptable on a computer may not reproduce





The publisher encourages the submission of articles in electronic form thus saving time and avoiding rekeying errors. A leaflet describing our requirements is available from the publisher upon request

CONTENTS
Direct

This journal is part of **ContentsDirect**, the *free* alerting service which sends tables of contents by e-mail for Elsevier books and journals. You can register for **ContentsDirect** online at: <http://contentsdirect.elsevier.com>

(Continued on last page of this issue)

- On the capacity of continuous powder classification in a gas-fluidized bed with horizontal sieve-like baffles. J.C. Bosma and A.C. Hoffmann 1
- Estimation of properties of ternary mixtures of solids using the mixing rule. M.A. Silva and M.N.N. Miranda 16
- The flow of powder into simple and stepped dies. G.-Y. Wu, L. Diharou and A.C.F. Cocks 24
- Physical and dielectric properties of pharmaceutical powders. G.M. McLoughlin, W.A.M. McMinn and T.R.A. Magee 40
- Synthesis of $\text{La}_2\text{O}_3/\text{BaCO}_3$ nanocatalysts and their catalytic performance. Y. He, B. Yang, G. Cheng and H. Pan 52
- Pore defects related to slurry character and their relevance to strength distribution in alumina ceramics. H. Abe, M. Naito, T. Hotta, H. Kamiya and K. Uematsu 58
- Recovery of copper powders from leach solutions containing copper by means of ammonia, sulphur dioxide and acetonitrile. S. Golak, T. Galban, M. Vesiljurt, D. Sergili and Z. Ekinci 65
- Importance of frictional forces on the formation of cavity in a packed bed under cross flow of gas. S. Rajneesh and G.S. Gupta 72
- Size segregation of binary mixture of solids in bubbling fluidized beds. L. Hullin, H. Yurong, D. Gidaspow, Y. Lidan and Q. Yukun 86
- Experimental and numerical investigation of the effect of buoyancy force on solid flow. T. Nouchi, A.B. Yu and K. Takeda 98
- Correlation of the breakage parameters with the critical surface tension for wetting of particle. M. Yekeler and A. Ozkan 108
- A six-parameter model to predict ash formation in a CFB boiler. Y. Hairui, M. Wirsum, Y. Guangxi, F.N. Felt and X. Youning 117

