MERRILL SKOLNIK

RADDAR HANDBOOK

SECOND EDITION



CONTENTS

Contributors xx Preface xxi

| Chap | ter 1. An Introduction to Radar Merrill I. Skolnik | 1.1 |
|------|---|--------------|
| 1.1 | Description of Radar | 1.1 |
| | Radar Block Diagram | 1.2 |
| 1.2 | Radar Equation | 1.6 |
| | Tracking | 1.8 |
| | Volume Search | 1.8 |
| | Jamming Clutter | 1.9 |
| 1.3 | | 1.10 |
| 1.3 | Range | 1.10 |
| | Radial Velocity | 1.11 1.11 |
| | Angular Direction | 1.11 |
| | Size | 1.12 |
| | Shape | 1.12 |
| | Other Target Measurements | 1.12 |
| 1.4 | Radar Frequencies | 1.13 |
| - | HF (3 to 30 MHz) | 1.15 |
| | VHF (30 to 300 MHz) | 1.15 |
| | UHF (300 to 1000 MHz) | 1.16 |
| | L Band (1.0 to 2.0 GHz) | 1.16 |
| | S Band (2.0 to 4.0 GHz) | 1.16 |
| | C Band (4.0 to 8.0 GHz) | 1.17 |
| | X Band (8.0 to 12.5 GHz) | 1.17 |
| | K _u , K, and K _a Bands (12.5 to 40.0 GHz) | 1.17 |
| | Millimeter Wavelengths (above 40 GHz) | 1.17 |
| | Laser Frequencies | 1.18 |
| 1.5 | Radar Nomenclature | 1.18 |
| | | |
| Chap | ter 2. Prediction of Radar Range Lamont V. Blake | 2.1 |
| 2.1 | | 2.1 |
| | Definitions | 2.1 |
| | Conventions | 2.2 |
| | Range Prediction Philosophy | 2.2 |
| | Historical Notes | 2.3 |
| 2.2 | Range Equations | 2.4 |
| | Radar Transmission Equation | 2.4 |
| | Maximum-Range Equation | 2.5 |
| | Pulse Radar Equation | 2.6 |
| | Detectability Factor | 2.6 |
| | Probabilistic Notation | 2.8 |

| | Automatic Detection | 2.8 |
|------|---|--------------|
| | Bistatic Radar Equation | 2.9 |
| | Equations in Practical Units | 2.9 |
| 2.3 | | 2.10 |
| | Transmitter Power and Pulse Length | 2.10 |
| | Antenna Gain, Efficiency, and Loss Factor | 2.11 |
| | Antenna Bandwidth | 2.12 |
| | Target Cross Section | 2.12 |
| | Wavelength (Frequency) | 2.13 |
| | Bandwidth and Matching Factors | 2.14 |
| 2.4 | Minimum Detectable Signal-to-Noise Ratio | 2.16 |
| | Integration of Signals | 2.17 |
| | Number of Pulses Integrated | 2.17 |
| | Evaluation of Probabilities | 2.18 |
| | Detector Laws | 2.23 |
| | Curves for Visual Detection | 2.24 |
| | Other Detection Methods | 2.25 |
| | Predetection Integration | 2.25 |
| 2.5 | System Noise Temperature | 2.26 |
| | Available Power, Gain, and Loss | 2.26 |
| | Noise Temperature | 2.27 |
| | The Referral Concept | 2.27 |
| | Antenna Noise Temperature | 2.28 |
| | Transmission-Line Noise Temperature | 2.30 |
| 2.0 | Receiver Noise Temperature | 2.31 |
| 2.6 | Pattern Propagation Factor | 2.31 |
| | General Discussion | 2.32 |
| | Mathematical Definition Pattern Factor | 2.35 |
| | A CONTRACT OF THE PROPERTY OF | 2.35 |
| | Reflection Coefficient | 2.36 |
| | Total Phase Difference | 2.37 |
| | Reflection from a Rough Spherical Surface | 2.38 |
| | Specular-Reflection Roughness Factor | 2.39 |
| | Spherical-Earth Reflection Geometry | 2.41 |
| | Divergence Factor | 2.42 |
| | Spherical-Earth Pattern Propagation Factor | 2.42 |
| | The Intermediate Region | 2.43 |
| | Elevation-Angle Interference-Region Calculation | 2.43 |
| 2.7 | Refraction and Coverage Diagrams Loss Factors | 2.44 2.46 |
| 2.1 | Antenna Pattern Loss | 2.46 |
| | Tropospheric-Absorption Loss | 2.40 |
| | Lens-Effect Loss | 2.52 |
| | Other Tropospheric Losses | 2.54 |
| | Procedure for Range-Dependent Losses | 2.54 |
| | Collapsing Loss | 2.54 |
| | Signal-Processing Losses | 2.55 |
| | Miscellaneous Losses | 2.56 |
| 2.8 | Jamming and Clutter | 2.56 |
| 2.0 | Jamming | 2.56 |
| | Clutter | 2.57 |
| | Targets in Clutter | 2.57 |
| 2.9 | Cumulative Probability of Detection | 2.60 |
| 2.10 | Accuracy of Radar Range Prediction | 2.60 |
| 2.11 | A Systematic Procedure for Range Prediction | 2.61 |
| 2.12 | Computer Solution of the Range Equation | 2.62 |
| | 로 2 : 마스크 10 등 1 : | |

| 11 (17) | | | |
|---------|----|------|----|
| (1 | ON | N | 10 |
| | | | |

vii

| Chap | ter 3. Receivers John W. Taylor, Jr. | 3.1 |
|------|---|------|
| 3.1 | The Configuration of a Radar Receiver | 3. |
| 3.2 | Noise and Dynamic-Range Considerations | 3.3 |
| | Definitions | 3.4 |
| | Evaluation | 3.5 |
| 3.3 | Bandwidth Considerations | 3.5 |
| | Definition | 3.5 |
| | Important Characteristics | 3.5 |
| 3.4 | Receiver Front End | 3.7 |
| | Configuration | 3.7 |
| | Effect of Characteristics on Performance | 3.7 |
| | Spurious Distortion of Radiated Spectrum | 3.7 |
| | Spurious Responses of Mixers Characteristics of Amplifiers and Mixers | 3.8 |
| 3.5 | Local Oscillators | 3.1 |
| 3.5 | Functions of the Local Oscillator | 3.1 |
| | Stalo Instability | 3.12 |
| | Coho and Timing Instability | 3.16 |
| | Total Radar Instability | 3.16 |
| 3.6 | Gain-Controlled Amplifiers | 3.17 |
| | Sensitivity Time Control (STC) | 3.17 |
| | Clutter Map Automatic Gain Control | 3.18 |
| | Automatic Noise-Level Control | 3.19 |
| 3.7 | | 3.19 |
| | Filtering of the Entire Radar System | 3.19 |
| | Definitions A Manual Elle | 3.20 |
| | Approximations to Matched Filters Filtering Problems Associated with Mixer Spurious Responses | 3.2 |
| 3.8 | | 3.22 |
| 3.0 | Characteristics | 3.25 |
| | Analog Logarithmic Devices | 3.27 |
| | Digital Logarithm | 3.28 |
| | Digital Log Power Combiner | 3.29 |
| 3.9 | | 3.30 |
| | Applications | 3.30 |
| | Characteristics | 3.30 |
| 3.10 | Phase Detectors and Synchronous Detectors | 3.32 |
| | Definitions and Characteristics | 3.32 |
| | Applications | 3.33 |
| | Examples of Phase Detectors | 3.36 |
| | Analog-to-Digital Phase Detector | 3.37 |
| 3.11 | Digital Phase Detector Analog-to-Digital Converter | 3.38 |
| 3.11 | Applications | 3.38 |
| | Formats | 3.39 |
| | Synchronization | 3.39 |
| | Performance Characteristics | 3.40 |
| | Multiplexing | 3.41 |
| 3.12 | I/Q Distortion Effects and Compensation Methods | 3.41 |
| | Gain or Phase Unbalance | 3.41 |
| | Time Delay and Pulse Shape Unbalance | 3.43 |
| | Nonlinearity in I and Q Channels | 3.45 |
| 2 40 | DC Offset | 3.46 |
| 3.13 | CFAR Detection Processes Application | 3.46 |
| | ADDICATION | 3 46 |

viii CONTENTS

| | Amplitude-Discrimination CFAR (Cell-Averaging CFAR) | 3.47 |
|-------|--|------|
| | Phase-Discrimination CFAR (CPACS) | 3.49 |
| | Effect on Range Resolution and Azimuth Accuracy | 3.50 |
| | Clutter Map CFAR | 3.53 |
| 3.14 | Diplex Operation | 3.54 |
| | Benefits | 3.54 |
| | Recommended Implementation | 3.54 |
| Chapt | ter 4. Transmitters T. A. Weil | 4.1 |
| 4.1 | Introduction | 4.1 |
| 4.1 | The Transmitter as Part of a Pulsed Radar System | 4.1 |
| | Why So Much Power? | 4.2 |
| | Why Pulsed? | 4.3 |
| 12 | Magnetron Transmitters | 4.5 |
| 4.2 | Limitations | 4.5 |
| | Magnetron Features | 4.6 |
| | Common Problems | 4.7 |
| 13 | Amplifier Chain Transmitters | 4.9 |
| 4.5 | Oscillator versus Amplifier | 4.9 |
| | Amplifier Chains: Special Considerations | 4.10 |
| 44 | RF Amplifier Tubes | 4.12 |
| 7.7 | Crossed-Field Amplifiers (CFAs) | 4.12 |
| | Klystrons | 4.14 |
| | Traveling-Wave Tubes (TWTs) | 4.15 |
| | RF Tube Selection | 4.17 |
| | RF Tube Power Capabilities | 4.21 |
| 4.5 | Combining and Arraying | 4.22 |
| 110 | Hybrid Combining (or Magic T) | 4.22 |
| | Phased Arrays | 4.23 |
| 4.6 | The state of the s | 4.25 |
| | Pulsed MTI Systems | 4.25 |
| | Pulse Compression Systems | 4.27 |
| | Stability Improvement by Feedback or Feedforward | 4.30 |
| 4.7 | | 4.31 |
| | Reduction of Spurious Outputs | 4.31 |
| | Reduction of Spectrum Amplitude Exceeding (sin x)/x | 4.31 |
| | Improvement over $(\sin x)/x$ by Means of Shaped Pulses | 4.31 |
| 4.8 | Pulse Modulators | 4.32 |
| | Line-Type Modulators | 4.33 |
| | Active-Switch Modulators | 4.35 |
| | Grid Pulsers | 4.39 |
| 4.9 | High-Voltage Crowbars, Regulators, and Power Supplies | 4.39 |
| | Crowbars | 4.40 |
| | Regulators | 4.41 |
| | High-Voltage Power Supplies | 4.41 |
| Chan | oter 5 Solid-State Transmitters Michael T. Borkowski | 5.1 |
| | | - |
| | Introduction | 5.1 |
| 5.2 | Solid-State Microwave Power Generation | 5.4 |
| | Microwave Bipolar Power Transistors | 5.5 |
| | Microwave Field-Effect Transistors (FETs) | 5.9 |
| | Millimeter-Wave Solid-State Power Sources | 5.11 |

CONTENTS

ix

| 5.3 | Solid-State Microwave Design | 5.12 |
|------|--|--------------|
| | High-Power Amplifier Design | 5.13 |
| | Phased Array Transceiver Module Design | 5.16 |
| | Microwave Monolithic Integrated Circuits | 5.16 |
| | Transceiver Module Performance Characteristics | 5.18 |
| 5.4 | Transmitter System Design | 5.21 |
| | Performance Sensitivities | 5.21 |
| | Power Combining | 5.23 |
| | Solid-State Transmitter Design Examples | 5.23 |
| hap | ter 6 Reflector Antennas Helmut E. Schrank, Gary E. Evans, | |
| | and Daniel Davis | 6.1 |
| 6.1 | Introduction | 6.1 |
| | Role of the Antenna | 6.1 |
| | Beam Scanning and Target Tracking | 6.1 |
| | Height Finding | 6.2 |
| | Classification of Antennas | 6.2 |
| 6.2 | | 6.2 |
| | Reciprocity | 6.2 |
| | Gain, Directivity, and Effective Aperture | 6.3 |
| | Radiation Patterns | 6.4 |
| 6.3 | Types of Antennas | 6.10 |
| | Paraboloidal Reflector Antennas | 6.12 |
| | Parabolic-Cylinder Antenna | 6.15 |
| | Shaped Reflectors | 6.17 |
| | Multiple Beams and Extended Feeds | 6.19 |
| | Monopulse Feeds | 6.21 |
| | Multiple-Reflector Antennas | 6.23 |
| | Special-Purpose Reflectors | 6.26 |
| | Feeds Reflector Automor Analysis | 6.26 |
| 0.0 | Reflector Antenna Analysis | 6.27 |
| 0.0 | Shaped-Beam Antennas | 6.30 |
| | Gain Estimation | 6.31 |
| | Shaped-Beam Antenna Design | 6.32 |
| | Antenna Size | 6.33 |
| 67 | Accuracy Design Considerations | 6.34 |
| 0.7 | Design Considerations | 6.34 |
| | Feed Blockage | 6.34 |
| | Feed Spillover and Diffraction | 6.37 |
| 60 | Surface Leakage Mechanical Considerations | 6.40 |
| | Radomes | 6.40 |
| 0.5 | Types of Radomes and General Considerations | 6.44 |
| | Environmental Effects | 6.44 |
| | Airborne and Missile Radomes | 6.45 |
| | Ground and Shipboard Radomes | 6.46 |
| | Other Radome Effects | 6.47 |
| 6 10 | Antenna Testing | 6.48 |
| 0.10 | Pattern Test Ranges | 6.52 |
| | Elevated Ranges | 6.52 |
| | Ground Ranges | 6.53 |
| | Compact Ranges | 6.55 |
| | Near-Field Ranges | 6.56 |
| | Miscellaneous Tests | 6.57 6.59 |
| | | 0.03 |

x CONTENTS

| Chapt | er 7 Phased Array Radar Antennas Theodore C. Cheston and Joe Frank | 7.1 |
|----------|---|--------------|
| 7.1 | Introduction | 7.1 |
| | Phased Array Radars | 7.1 |
| | Scanning of Arrays | 7.7 |
| | Array Theory | 7.10 |
| 7.3 | Planar Arrays and Beam Steering | 7.17 |
| | Planar Arrays | 7.17 |
| | Element-Phasing Calculations | 7.21 |
| 7.4 | Aperture Matching and Mutual Coupling | 7.22 |
| | Significance of Aperture Matching | 7.22 |
| | Effects of Mutual Coupling | 7.23 |
| | Element Pattern | 7.25 |
| | Thinned Arrays | 7.26 |
| | Impedance Variation of Free Space | 7.27 |
| | Element Impedance | 7.27 |
| | Analytical Techniques | 7.29 7.30 |
| | Nonisolating Feeds | 7.30 |
| | Mutual Coupling and Surface Waves | 7.31 |
| | Array Simulators | 7.35 |
| | Compensation for Scanned Impedance Variation | 7.35 |
| | Small Arrays | 7.37 |
| 7.5 | Low-Sidelobe Phased Arrays | 7.37 |
| | Illumination Functions | 7.38 |
| | Effect of Errors | 7.39 |
| | Random Errors | 7.43 |
| 7.6 | Quantization Effects | 7.43 |
| | Phase Quantization | 7.45 |
| | Periodic Errors | 7.49 |
| 1.7 | Bandwidth of Phased Arrays | 7.49 |
| | Aperture Effects Feed Effect | 7.51 |
| | Broad Instantaneous Bandwidth | 7.53 |
| | Time-Delay Networks | 7.56 |
| 7.0 | Feed Networks (Beamformers) | 7.58 |
| | Phase Shifters | 7.63 |
| 7.9 | Diode Phasers | 7.63 |
| | Ferrite Phasers | 7.64 |
| 7 10 | Solid-State Modules | 7.67 |
| | Phased Array Systems | 7.69 |
| Chan | ter 8 Automatic Detection, Tracking, and Sensor Integration | |
| Onap | G. V. Trunk | 8.1 |
| | | |
| 11/200 | Introduction | 8.1 |
| 8.2 | Automatic Detection | 8.1 8.2 |
| | Optimal Detector | 8.2 |
| | Practical Detectors | 100 |
| | False-Alarm Control | 8.12 8.21 |
| | Target Resolution | 8.23 |
| 12/11/20 | Detection Summary | 8.23 |
| 8.3 | Automatic Tracking | 8.24 |
| | Track-While-Scan Systems | 8.38 |
| | | |

| CONTENTS | CONTENT | S |
|----------|---------|---|
|----------|---------|---|

χi

| 8.4 | Multisensor Integration Colocated Radar Integration Multisite Radar Integration Unlike-Sensor Integration | 8.40 8.42 8.43 8.44 |
|-------|---|------------------------------|
| Chap | ter 9 Electronic Counter-Countermeasures A. Farina | 9.1 |
| | Introduction | 9.1 |
| 9.2 | | 9.2 |
| 9.3 | Electronic Warfare Support Measures Electronic Countermeasures | 9.2 |
| 9.5 | | 9.4 |
| | Antenna-Related ECCM | 9.7 |
| 0.0 | Sidelobe-Blanking (SLB) System | 9.7 9.9 |
| | Sidelobe Canceler (SLC) System | 9.11 |
| | Adaptive Arrays | 9.14 |
| 9.7 | Transmitter-Related ECCM | 9.16 |
| | Receiver-Related ECCM | 9.18 |
| 9.9 | Signal-Processing-Related ECCM | 9.19 |
| | Operational-Deployment Techniques | 9.21 |
| 9.11 | Francis of Loominguou | 9.22 |
| | Surveillance Radars Tracking Radars | 9.23 |
| 9 12 | ECCM and ECM Efficacy | 9.25 |
| 3.12 | The Radar Equation in Jamming and Chaff Conditions | 9.26 |
| | The Hadar Equation in Samming and Chair Conditions | 9.28 |
| | | |
| Chapt | ter 10 Pulse Compression Radar Edward C. Farnett and | |
| | George H. Stevens | 10.1 |
| 10.1 | Introduction | 10.1 |
| | Factors Affecting Choice of Pulse Compression System | 10.1 |
| | Linear FM | 10.4 |
| 10.4 | | 10.4 |
| 10.5 | Pulse Compression Devices | 10.6 |
| | Digital Pulse Compression | 10.7 |
| | Surface-Wave Pulse Compression | 10.10 |
| | Other Passive Linear-FM Devices | 10.12 |
| 10.6 | Voltage-Controlled Oscillator | 10.15 |
| 10.6 | Phase-Coded Waveforms Optimal Binary Sequences | 10.15 |
| | Maximal-Length Sequences | 10.17 |
| | Quadratic Residue Sequences | 10.19 10.21 |
| | Complementary Sequences | 10.21 |
| | Implementation of Biphase-Coded Systems | 10.21 |
| | Doppler Correction | 10.24 |
| | Polyphase Codes | 10.25 |
| 10.7 | Time-Frequency-Coded Waveforms | 10.26 |
| 10.8 | Weighting and Equalization | 10.27 |
| | Paired Echoes and Weighting | 10.27 |
| | Comparison of Weighting Functions | 10.29 |
| | Taylor versus Cosine-Squared-Plus-Pedestal Weighting | 10.31 |
| | Taylor Weighting with Linear FM | 10.31 |
| | Discrete Time Weighting Amplitude and Phase Distortion | 10.34 |
| | Amphitude and Fridse Distortion | 10.34 |

| | Equalization | 10.36 |
|-------|--|----------------|
| Chapt | er 11 Radar Cross Section Eugene F. Knott | 11.1 |
| | | 11.1 |
| 11.1 | Introduction | 11.1 |
| 11.2 | The Concept of Echo Power | 11.2 |
| | Definition of RCS | 11.4 |
| 44.0 | Examples of RCS Characteristics RCS Prediction Techniques | 11.18 |
| 11.3 | Exact Methods | 11.20 |
| | Approximate Methods | 11.24 |
| 11 / | RCS Measurement Techniques | 11.34 |
| 11.4 | General Requirements | 11.35 |
| | Outdoor Test Ranges | 11.38 |
| | Indoor Test Ranges | 11.39 |
| 11.5 | Echo Reduction | 11.43 |
| | Shaping | 11.44 |
| | Radar Absorbers | 11.46 |
| 11.6 | Summary | 11.51 |
| Chap | ter 12 Ground Echo Richard K. Moore | 12.1 |
| 252.5 | | 12.1 |
| 12.1 | | 12.1 |
| | Relative Importance of Theory and Empiricism | 12.3 |
| 122 | Available Scattering Information Parameters Affecting Ground Return | 12.4 |
| | Theoretical Models and Their Limitations | 12.6 |
| 12.3 | Descriptions of a Surface | 12.6 |
| | Simplified Models | 12.7 |
| | Physical Optics Models | 12.9 |
| | Small-Perturbation and Two-Scale Models | 12.10 |
| | Other Models | 12.12 |
| 12.4 | Fading of Ground Echoes | 12.12 |
| | Fading-Rate Computations | 12.13 |
| | Effect of Detection | 12.16 |
| | Moving Target Surfaces | 12.18 |
| 12.5 | Measurement Techniques for Ground Return | 12.18 |
| | CW and FM-CW Systems | 12.18 |
| | Range-Measuring Systems | 12.21 |
| | CW-Doppler Scatterometers | 12.22 12.23 |
| | Independent Samples Required for Measurement Accuracy | 12.23 |
| | Near-Vertical Problem | 12.23 |
| | Ground and Helicopter Scatterometers and Spectrometers | 12.24 |
| | Scattering Coefficient from Images | 12.28 |
| 12.6 | Bistatic Measurements General Models for Scattering Coefficient (Clutter Models) | 12.28 |
| | | 12.35 |
| 12.7 | Effects of Roughness, Moisture Content, and Vegetation Cover | 12.35 |
| | Soil Moisture | 12.39 |
| | Vegetation | 12.41 |
| | Snow | 12.42 |
| | Sea Ice | 12.44 |
| 12.8 | CONTRACTOR SECTION AND ADDRESS OF THE CONTRACTOR SECTION AND ADDRESS OF THE CONTRACTOR AND ADDRESS OF THE CONTRACTOR ADDRE | 12.45 |
| | | |

| CONTENTS | xiii |
|----------|------|
| | |

| Chap | ter 13 Sea Clutter Lewis B. Wetzel | 13.1 |
|-------------------------|--|-------|
| 13.1 | Introduction | 13.1 |
| | Description of the Sea Surface | 13.2 |
| | The Wave Spectrum | 13.3 |
| | General Sea Descriptors | 13.5 |
| 13.3 | Empirical Behavior of Sea Clutter | 13.6 |
| 100000 | Dependence on Wind Speed, Grazing Angle, and Frequency | 13.8 |
| | The Spectrum of Sea Clutter | 13.21 |
| | Other Effects on Sea Clutter | 13.23 |
| 13.4 | Theories of Sea Clutter | 13.27 |
| | Theories Based on Global Boundary-Value Problems | 13.29 |
| | The Composite-Surface Hypothesis | 13.32 |
| | Scattering by Surface Features | 13.33 |
| 13.5 | Summary and Conclusions | 13.36 |
| | | |
| Chap | ter 14 CW and FM Radar William K. Saunders | 14.1 |
| 14.1 | Introduction and Advantages of CW | 14.1 |
| 14.2 | Doppler Effect | 14.2 |
| 14.3 | Unmodulated CW Radar | 14.2 |
| | Spectral Spreading | 14.2 |
| | Noise in Sources | 14.3 |
| | Noise from Clutter | 14.3 |
| | Microphonism | 14.7 |
| | Scanning and Target Properties | 14.7 |
| 14.4 | Sources | 14.8 |
| | Master Oscillator Power Amplifier (MOPA) Chains | 14.8 |
| | Active Stabilization | 14.8 |
| | Stabilization of Power Oscillators | 14.11 |
| | Noise Measurement Technique | 14.11 |
| 14.6 | Receivers | 14.15 |
| | RF Amplification | 14.15 |
| | Generation of the Local-Oscillator Signal | 14.15 |
| | IF Amplifier | 14.16 |
| | Subcarriers | 14.16 |
| | Amplication | 14.18 |
| | Doppler Filter Banks | 14.18 |
| | Doppler Trackers | 14.18 |
| | Constant False-Alarm Rate (CFAR) | 14.19 |
| | Minimization of Feedthrough | 14.19 |
| 14.8 | Miscellaneous CW Radars | 14.20 |
| | CW Proximity Fuzes | 14.20 |
| | Police Radars | 14.21 |
| | FM Radar | 14.21 |
| 14.10 | Sinusoidal Modulation | 14.23 |
| | Double Sinusoidal Modulation | 14.26 |
| | Triangular and Sawtooth Modulation | 14.27 |
| | Noise Modulation | 14.28 |
| ACCURATION AND ADDRESS. | Coded Modulations | 14.29 |
| | Dual Modulation | 14.30 |
| | Leakage | 14.30 |
| | Performance of FM-CW Systems | 14.31 |
| 14.17 | Short-Range Systems and Microwave Proximity Fuzes | 14.31 |

xiv CONTENTS

| 14.18 | Altimeters | 14.34 |
|-------|--|----------------|
| 14.19 | Doppler Navigators | 14.37 |
| 14.20 | Personnel Detection Radar and Miscellaneous FM-CW Systems | 14.39 |
| 14.21 | Tailoring the Range Response of FM-CW Systems | 14.41 |
| Chap | ter 15 MTI Radar William W. Shrader and | |
| | V. Gregers-Hansen | 15.1 |
| 15.1 | | 15.1 |
| | Moving-Target Indicator (MTI) Block Diagram | 15.3 |
| | Moving-Target Detector (MTD) Block Diagram | 15.5 |
| | Clutter Filter Response to Moving Targets | 15.7 |
| 15.3 | Clutter Characteristics | 15.8 |
| | Spectral Characteristics | 15.8 |
| | Amplitude Characteristics | 15.10 |
| 15.4 | • | 15.11 |
| | Improvement Factors (I) | 15.11 |
| | Signal-to-Clutter Ratio Improvement (I _{SCR}) | 15.11 |
| | Subclutter Visibility (SCV) | 15.13 |
| | Interclutter Visibility (ICV) | 15.13 |
| | Filter Mismatch Loss | 15.14 |
| 45.5 | Clutter Visibility Factor (V_{oc}) | 15.14 |
| | Improvement Factor Calculations | 15.14 |
| | Optimum Design of Clutter Filters | 15.16 |
| | MTI Clutter Filter Design | 15.23 |
| 15.8 | Clutter Filter Bank Design | 15.29 |
| | Empirical Filter Design | 15.29 |
| | Chebyshev Filter Bank | 15.31 |
| 15.0 | Fast Fourier Transform Filter Bank | 15.34 |
| 15.9 | Staggered PRF | 15.34 |
| | Stagger Design Procedures | 15.34 |
| | Feedback and Pulse-to-Pulse Staggering | 15.37 |
| | Improvement Factor Limitation Caused by Staggering | 15.39 |
| | Time-Varying Weights | 15.40 |
| 1E 10 | Depth of First Null in Velocity Response | 15.40 |
| 15.10 | Improvement Factor Restriction Caused by Limiting Radar System Stability and A/D Quantization Requirements | 15.41 |
| 15.11 | | 15.45 |
| | System Instabilities Effect of Quantization Noise on Improvement Factor | 15.45 |
| | Pulse Compression Considerations | 15.53 |
| 15 12 | Analog-to-Digital Conversion Considerations | 15.55 |
| 13.12 | Dynamic Range | 15.57 15.58 |
| | I and Q Balance Requirements | 15.59 |
| | Timing Jitter | 15.60 |
| | Linearity | 15.60 |
| | Accuracy | 15.60 |
| 15 13 | Adaptive MTI Implementation | 15.61 |
| | Clutter Map Implementation | 15.65 |
| | Considerations Applicable to MTI Radar Systems | 15.69 |
| 10.10 | Considerations Applicable to Will Radar Systems | 15.05 |
| Chapt | ter 16 Airborne MTI Fred M. Staudaher | 16.1 |
| 16.1 | Systems Using Airborne MTI Techniques | 16.1 |
| | Coverage Considerations | 16.2 |
| 16.3 | Platform Motion and Altitude Effects on MTI Performance | 16.2 |
| | Effect of Slant Range on Doppler Effect | 16.4 |

CONTENTS

| | TACCAR | 16.5 |
|-------|--|----------------|
| | Platform-Motion Effect | 16.7 |
| 16.4 | | 16.8 |
| | Physically Displaced Phase-Center Antenna | 16.8 |
| | Electronically Displaced Phase-Center Antenna | 16.10 |
| | Power in the Antenna Sidelobes | 16.13 |
| 16.5 | Scanning-Motion Compensation | 16.14 |
| 52.2 | Compensation-Pattern Selection | 16.16 |
| 16.6 | | 16.17 |
| 16.7 | Platform-Motion Compensation, Forward Direction | 16.20 |
| 16.8 | | 16.23 |
| | Performance Capability of Space-Time Adaptive Arrays | 16.26 |
| 16.9 | | 16.28 |
| | Effect of Multiple Spectra | 16.29 |
| 16.11 | Detection of Ground Moving Targets | 16.29 |
| | | |
| Chap | ter 17 Pulse Doppler Radar William H. Long, | |
| | David H. Mooney, and William A. Skillman | 17.1 |
| 17.1 | Characteristics and Applications | 17.1 |
| | Nomenclature | 17.1 |
| | Applications | 17.1 |
| | PRFs | 17.1 |
| | Pulse Doppler Spectrum | 17.2 |
| | Ambiguities and PRF Selection | 17.5 |
| | Basic Configuration | 17.7 |
| 17.2 | Pulse Doppler Clutter | 17.9 |
| | General | 17.9 |
| | Ground Clutter in a Stationary Radar | 17.9 |
| | Ground Clutter in a Moving Radar | 17.9 |
| | Clutter Return: General Equations | 17.10 |
| | Sidelobe Clutter | 17.11 |
| | Sidelobe Discretes | 17.11 |
| | Main-Beam Clutter | 17.16 |
| | Main-Beam Clutter Filtering | 17.16 |
| | Altitude-Line Clutter Filtering | 17.18 |
| 17.3 | The planting of the planting o | 17.19 |
| | Transmitted-Pulse Suppression | 17.19 |
| | Range Gating | 17.19 |
| 17.4 | Range-Ambiguity Resolution | 17.19 |
| | High-PRF Ranging | 17.20 |
| | Medium-PRF Ranging | 17.25 |
| 17.5 | | 17.25 |
| 17.0 | Single-Target Tracking | 17.25 |
| | Multiple-Target Tracking | 17.26 |
| 17.6 | | |
| 17.0 | Dynamic-Range and Stability Requirements Dynamic Range | 17.26 17.26 |
| | Stability Requirements | 17.28 |
| | Types of Spurious Modulation | 17.28 |
| | Sinusoidal Modulations | 17.29 |
| | Pulse-to-Pulse Random Modulation | |
| 177 | Range Performance | 17.33 |
| 17.7 | 9 | 17.33 |
| | Range Equation | 17.33 |
| | System Losses | 17.33 |

xvi CONTENTS

| | Probability of False Alarm | 17.35 |
|-------|--|----------------|
| | Probability of Detection | 17.36 |
| Chapt | er 18 Tracking Radar Dean D. Howard | 18.1 |
| 18.1 | Introduction | 18.1 |
| 18.2 | Scanning and Lobing | 18.3 |
| 18.3 | Monopulse (Simultaneous Lobing) | 18.8 |
| | Amplitude-Comparison Monopulse | 18.9 |
| | Phase-Comparison Monopulse | 18.17 |
| | Monopulse Tracking with Phased Arrays | 18.19 |
| | One- and Two-Channel Monopulse | 18.19 |
| | Conopulse | 18.21 |
| 18.4 | Servosystems for Tracking Radar | 18.22 |
| 18.5 | Target Acquisition and Range Tracking | 18.26 |
| | Acquisition | 18.26 |
| | Range Tracking | 18.27 |
| | nth-Time-Around Tracking | 18.30 |
| 18.6 | | 18.30 |
| | High-Range-Resolution Monopulse | 18.30 |
| | Dual-Band Monopulse | 18.31 |
| | Mirror Antenna (Inverse Cassegrain) | 18.32 |
| | On-Axis Tracking | 18.33 |
| 18.7 | Sources of Error | 18.33 |
| 18.8 | | 18.34 |
| | Amplitude Noise | 18.34 18.37 |
| | Angle Noise (Glint) | 18.43 |
| | Range Noise (Range Glint) | 18.45 |
| 10.0 | Doppler Scintillation | 18.46 |
| 18.9 | | 18.46 |
| | Multipath Crosstalk Caused by Cross-Polarized Energy | 18.48 |
| | Troposphere Propagation | 18.49 |
| 10 10 | Internal Sources of Error | 18.50 |
| 10.10 | Receiver Thermal Noise | 18.50 |
| | Other Internal Sources of Error | 18.52 |
| 18.11 | Summary of Sources of Error | 18.53 |
| 10.11 | Angle Measurement Errors | 18.53 |
| | Range Measurement Errors | 18.54 |
| 18.12 | Error Reduction Techniques | 18.54 |
| | Multipath-Error Reduction | 18.54 |
| | Target Angle and Range Scintillation (Glint) Reduction | 18.57 |
| | Reduction of Internally Caused Errors | 18.57 |
| | | |
| Chap | ter 19 Radar Guidance of Missiles Alex Ivanov | 19.1 |
| 19.1 | Introduction | 19.1 |
| 19.2 | Overview of Semiactive CW Systems | 19.3 |
| | Doppler Frequency Relationships | 19.3 |
| | Clutter and Feedthrough Considerations | 19.6 |
| | Guidance Fundamentals | 19.7 |
| | Target Illumination | 19.9 |
| 19.3 | System Evolution | 19.9 |
| | Racic Samiactive Seeker | 19 10 |

xvii

| | Unambiguous (Offset Video) Receiver | 19.10 |
|-------|--|----------------|
| | Inverse Receiver | 19.12 |
| | Angle Tracking: Conical Scan to Monopulse | 19.14 |
| | Pulse Doppler (PD) Operation | 19.15 |
| | Active Seekers | 19.15 |
| | Passive Seekers | 19.17 |
| | Other System Considerations | 19.20 |
| 19.4 | System Functional Operation | 19.21 |
| | Reference-Channel Operation | 19.21 |
| | Target Signal Detection | 19.23 |
| | Target Signal Tracking | 19.26 |
| | Performance Limitations | 19.29 |
| 19.5 | Subsystems and Integration | 19.31 |
| | Radome | 19.32 |
| | Antenna | 19.33 |
| | Receiver | 19.35 19.37 |
| | Low-Noise Frequency Reference | 19.37 |
| | Signal Processing Transmitter | 19.38 |
| | Power | 19.40 |
| | Integration | 19.40 |
| | integration | 15.40 |
| Chapt | ter 20 Height Finding and 3D Radar David J. Murrow | 20.1 |
| 20.1 | Height Finding Radars and Techniques | 20.1 |
| | Early Radar Techniques for Height Finding | 20.1 |
| | Height Finding Techniques in 3D Radars | 20.6 |
| 20.2 | Derivation of Height from Radar Measurements | 20.14 |
| | Flat-Earth Approximation | 20.14 |
| | Spherical Earth: Parabolic Approximation | 20.14 |
| | Spherical Earth: Exact Geometry | 20.14 |
| | Corrections for Atmospheric Refraction | 20.14 |
| | Practical Corrections | 20.19 |
| 20.3 | Height Accuracy Performance Limitations | 20.19 |
| | Fundamental Accuracy of Sequential Lobing | 20.20 |
| | Fundamental Accuracy of Simultaneous Lobing | 20.25 |
| | Elevation Error Due to Surface Reflections | 20.32 |
| | Low-Angle Squinted-Beam Height Finding | 20.36 |
| Chap | ter 21 Synthetic Aperture Radar L. J. Cutrona | 21.1 |
| 21.1 | Basic Principles and Early History | 21.1 |
| 21.2 | | 21.4 |
| | Conventional Technique | 21.4 |
| | The Unfocused Synthetic Aperture | 21.5 |
| | The Focused Case | 21.6 |
| 21.3 | | 21.7 |
| 21.4 | Signal-Processing Theory | 21.8 |
| | Detailed Resolution Analysis | 21.8 |
| | Signal-to-Noise-Ratio Considerations | 21.15 |
| | Effect of Phase Errors | 21.17 |
| | Signal Processing | 21.17 |
| 21.5 | Additional System Considerations | 21.18 |
| | Antenna | 21.18 |

xviii CONTENTS

| | Receiver-Transmitter | | 21.19 |
|-------|---|---|----------------|
| | Storage and Recording | | 21.19 |
| | Motion Compensation | | 21.20 |
| | Squint Mode | | 21.20 |
| | Spotlight Mode | | 21.21 |
| | Effects of Motion Errors | | 21.21 |
| | Multiple-Beam Radars | | 21.21 |
| | ISAR | | 21.21 |
| | Three-Dimensional Spectrum | | 21.21 |
| Chapt | er 22 Space-Based Radar Systems and Technology | | |
| | Leopold J. Cantafio | | 22.1 |
| | Introduction | | 22.1 |
| 22.2 | SBR Systems Considerations | | 22.1 |
| | Types of SBR | | 22.1 |
| | Considerations | | 22.5 |
| 22.3 | SBR System Descriptions | | 22.14 |
| | STS Rendezvous Radar | | 22.14 |
| | Seasat-A Synthetic Aperture Radar | | 22.15 |
| | Shuttle Imaging Radar | | 22.15 |
| | GEOS-C SBR System Characteristics | | 22.15 22.17 |
| 00.4 | U.S.S.R. Cosmos 1500 Side-Looking Radar | | 22.17 |
| 22.4 | Technology Antennas | | 22.18 |
| | Transmit/Receive Modules | | 22.23 |
| | On-Board Processors | | 22.24 |
| | Prime Power | | 22.24 |
| 22.5 | Critical Issues | | 22.26 |
| LLIO | SBR System Costs | | 22.26 |
| | Survivability and Vulnerability | | 22.26 |
| 22.6 | SBR Future Possibilities | | 22.26 |
| | Rendezvous Radar Missions | | 22.26 |
| | Remote-Sensing Missions | | 22.29 |
| | Global Air Traffic Surveillance | | 22.30 |
| | Military SBR Systems | | 22.31 |
| Chap | ter 23 Meteorological Radar Robert J. Serafin | | 23.1 |
| 23.1 | Introduction | | 23.1 |
| | The Radar Range Equation for Meteorological Targets | | 23.2 |
| | Design Considerations | | 23.5 |
| 20.0 | Attenuation Effects | | 23.5 |
| | Range and Velocity Ambiguities | | 23.10 |
| | Ground Clutter Effects | | 23.11 |
| | Typical Weather Radar Designs | | 23.12 |
| 23.4 | | | 23.13 |
| | Measurement Accuracy | , | 23.15 |
| | Processor Implementations | | 23.17 |
| 23.5 | | | 23.17 |
| | Precipitation Measurement | | 23.18 |
| | Severe Storm Warning | | 23.19 |
| 23.6 | | | 23.23 |
| | Multiple-Parameter Radar | | 13.7 |

| CONTENTS | | |
|----------|--|--|
|----------|--|--|

xix

| | Multiple Radars | 23.24 |
|-------|--|----------------|
| | Rapid Scanning | 23.25 |
| | Airborne and Space-Borne Radars | 23.26 |
| | Clear-Air Radars | 23.27 |
| | Synthetic Aperture Radar and Pulse Compression | 23.28 |
| | Syntholic reportation of the second of the s | |
| Chapt | er 24 HF Over-the-Horizon Radar J. M. Headrick | 24.1 |
| 24.1 | Introduction | 24.1 |
| | Radar Equation | 24.3 |
| | Transmitters | 24.4 |
| 24.4 | Antennas | 24.5 |
| 24.5 | Clutter: The Echo from the Earth | 24.6 |
| 24.6 | Radar Cross Section | 24.10 |
| 24.7 | Noise and Interference | 24.12 |
| 24.8 | Spectrum Use | 24.14 |
| 24.9 | Sky-Wave Transmission Medium | 24.15 |
| | Sky-Wave Radar Performance | 24.22 |
| 24.11 | Receiver-Processor | 24.36 |
| 24.12 | Ground-Wave Radar Performance | 24.38 |
| Chap | ter 25 Bistatic Radar Nicholas J. Willis | 25.1 |
| 25.1 | Concept and Definitions | 25.1 |
| | History | 25.2 |
| | Coordinate System | 25.3 |
| | Range Relationships | 25.6 |
| - | Range Equation | 25.6 |
| | Ovals of Cassini | 25.6 |
| | Operating Regions | 25.7 |
| | Isorange Contours | 25.8 |
| 25.5 | Area Relationships | 25.9 |
| | Location | 25.9 |
| | Coverage | 25.10 |
| | Clutter Cell Area | 25.12 |
| 25.6 | Doppler Relationships | 25.13 |
| | Target Doppler | 25.13 |
| | Isodoppler Contours | 25.14 |
| 25.7 | Target Cross Section | 25.14 |
| | Pseudo-Monostatic RCS Region | 25.15 |
| | Bistatic RCS Region | 25.17 |
| | Glint Reduction in the Bistatic RCS Region | 25.17 |
| | Forward-Scatter RCS Region | 25.17 |
| 25.8 | Clutter | 25.18 |
| | In-Plane Land Clutter Scattering Coefficient | 25.21 |
| | In-Plane Sea Clutter Scattering Coefficient | 25.24 |
| | Out-of-Plane Scattering Coefficient | 25.24 |
| 25.9 | Special Techniques, Problems, and Requirements | 25.24 |
| | Pulse Chasing | 25.24 |
| | Beam Scan on Scan | 25.26 |
| | Sidelobe Clutter | 25.27 |
| | Time Synchronization | 25.27 25.28 |
| | Phase Synchronization and Stability | 25.28 |